

www.hzyongchao.com info@hzyongchao.com



## UNIVERSAL JOINT CARDAN SHAFTS



Original Equipment Quality ISO9001



## Introduction

Since 2000, YONGCHAO is established as a factory which produces U-joint for Automotive and Industrial applications. For now, there are more than 450 U-joint items in the product list for Passenger Cars, Light Trucks & SUVs, Heavy Duty Trucks, Construction Machinery and Agriculture Machinery. The Shaft parts mainly for Heavy Duty Trucks and Construction Machinery are also in the production. For better and faster supplying to East Asial market, South Korea branch of YONGCHAO is found in 2011.

Strict quality controlling is one of the important reason for fast growing of YONGCHAO. Our products are certified by ISO 9001/2008 standard. And some testing machines as Roundtest, Contracer and Surftest are imported from Mitutoyo of Japan to guarantee the stability of quality.

Although we have stock of the common items, we still do special design for customer's request, this is the other important reason. Through the effective communication, YONGCHAO make the modification of the items to support customers. This support assist them to satisfy the local special needs and expand the market share.

YONGCHAO is the OEM supplier of ZF, Zoonlion and KIA, and we have well sold to Germany, America, Korea, South Africa, Italy, Russia, the Middle East etc..

The rules of High quality, fast delivery and reasonable price are critically operated in YONGCHAO's daily activities. YONGCHAO is a young but dynamic company, we are looking forward to cooperate with you to make a better future.















## Nylon Washers Keep more grease inside, promote the wear-resisting property and lower the overall operating temperature.

Obtain a hardness of 60-66 HRC after the heat treatment then the exact dimensions for loading capacity.

Internal Triple Lip Seals Keep maximun grease in and contaminants out in a wider range of environments.

Dust Caps
Provide a extra
shield to stop
the
contaminates

Bearing Cups
Made as 58-64 HRC of surface
hardness in a precision dimension
to fit a yoke.

## Grease

With pre-lubrication at the factory with EP (Extreme Pressure) NLGI grade 2 grease in an operating range of -50°C to 160°C.

Journal surface
Grinding operate a smooth surface to reduce wear.

Double Grease Nipple With two directions for easier relubrication during preventive maintenance.

Hot Forging Crosses
Cross are made as 58-64 HRC of surface hardness and 28-45 HRC of core hardness with a high quality steel which provide the U-joint for a strength and long life.







www.hzyongchao.com

info@hzyongchao.com