KREAT CONTACT DETAILS

Yunnan KREAT Engineering Machinery Equipment Co., Ltd. (Yanglin Manufacturing Base)
Add: No.1 Jinshan Road, Yanglin Industrial Park, Songming County, Kunming, Yunnan, China.
Tel: 400-0871-528
Email: info@ynkreat.com

Yunnan KREAT heavy industry co.,ltd. (Qujing factory)
Add: Hongqiao Advanced Equipment Manufacturing Area, Malong Industrial Park, Quqing City, Yunnan Province
Tel: 400-0871-528
Email: info@ynkreat.com

www.kreatgroup.com
Email: info@ynkreat.com

CONNECT WITH US

@KREAT Group @KREAT Group @KREAT Group
@KREAT Group @KREAT Group @KREAT Group
@KREAT Group @KREAT Group

The material in this document is for information only and is subject to change without notice.
Due to continual product development we reserve the right to change specifications without notice.
KREAT® assumes no liability resulting from errors or omissions in this document, or from the use of the information contained herein.
Product performance figures given in this brochure are for guidance purposes only, this information does not constitute an expressed or implied warranty or guarantee.
Results will vary depending on conveyor settings, feed source and types of material being processed.
Images are for illustrative purposes only, some or all of the machines in the illustrations may be fitted with optional extras.
Please check with your Dealer for details on optional extras.
Copyright 2026 KREAT®. Published and Printed in February 2026.
Effective date: Jun. 2026. Product parameters are subject to change without notice or responsibility. The pictures and drawings in this manual are for illustration only all rights reserved in Kreat.



WE SPECIALIZE EXCLUSIVELY IN 5-HIGHLIGHT CRUSHING AND SCREENING

94,570 ㎡ +
Manufacturing base

1000 +
Project certification

200 +
Core talent

Welcome to the world of KREAT

As a nationally certified high-tech company and a hidden champion in the field of specialized and innovative manufacturing, KREAT Group is committed to developing high-end crushing and screening equipment.

The core product lineup includes track-mounted mobile crushing and screening equipment-such as jaw, cone, impact, VSI, HSI and double- roll crushers, inclined screen, horizontal screen and scalping screen, among other crushing and screening solutions. These products are widely used in quarry and mining, construction project, the recycling, demolition, aggregates processing, and other related fields.

KREAT provides customers with professional, timely, and considerate all-round services. The company maintains a team of service engineers and operators, a nationwide parts warehouses and several service branches. It also offers dedicated hotlines for prompt online support.

With the "K6" after-sales service system, KREAT ensures stable equipment operation and delivers practical solutions to customer issues. So far, KREAT's services have reached customers and agents on multiple continents and in major countries and regions worldwide.

DEDICATION MAKES PROFESSION

We specialize exclusively in crushing and screening, guided by our “5 Highlights”:
Stable direction – keeping our course steady
Stable technology – ensuring reliable and proven solutions
Stable quality – delivering consistent, high-standard products
Stable delivery – meeting commitments on time
Stable service – providing dependable support throughout

We strive to “achieve a depth of ten thousand meters in a field that is only one meter wide,” and we are committed to becoming a world□class enterprise in the crushing and screening industry.

KREAT Product Range

Jaw series

05-06 Page

- KJ-1170 — External power
- KJ-1170E — Dual power
- KJ-1170H — Diesel hydraulic
- KJ-1280 — External power
- KJ-1280E — Dual power
- KJ-1290 — External power
- KJ-1290H — Diesel hydraulic



Impact series

07 Page

- KI-1213RS — External power
- KI-1213ERS — Dual power
- KI-1214RS — External power
- KI-1214E — Dual power
- KI-1214DRS — Direct Drive



Cone series

08 Page

- KC-440RS — External power
- KC-440ERS — Dual power
- KC-300RS — External power
- KC-300ERS — Dual power
- KC-300HRS — Diesel hydraulic
- KC-400RS — External power



VSI series

9 Page

- KPR-320RS — External power
- KPV-7150RS — External power



Screen series

10-12 Page

- KS-133 — External power
- KS-133E — Dual power
- KS-933H — Diesel hydraulic
- KSH-6203 — External power
- KSH-6203HR — Diesel hydraulic
- KSZ-500H — Diesel hydraulic
- KSZ-600H — Diesel hydraulic
- KSZ-800E — Dual power



Auxiliary series

13 Page

- Tracked mobile stacker KMC-1023H
- Modular sand wash&screen KXT-120M
- Modular powder control machine KDU-75M



Modular series

15 Page

- KJ-1170M — External power
- KJ-1280M/1290M — External power
- KI-1213MRS — External power
- KC-300MRS/400MRS — External power
- KC-440MRS — External power
- KS-133M — External power



External power : Diesel engine for hydraulic system(tracks, cylinders), need external power supply(power grid or external generator) for crushing.

Dual power : Diesel engine+generator, can running by generator itself or external power supply(power grid or external generator) for crushing, can only choose one out of two electric power source.

Diesel hydraulic : Crushing&hydraulic system running by diesel engine.

Direct drive : Diesel engine+generator, crusher unit running by diesel engine, other components running by small generator itself.

KREAT
Jaw series

Machines in this range include:

■ KJ-1170 / 1170E / 1170H ■ KJ-1280 / 1280E ■ KJ-1290 / 1290H

KREAT KJ series jaw crushers are designed to meet the initial crushing needs of customers in the mining, quarrying, and recycling industries. These machines are one of the most advanced and reliable in the market, with high productivity in various applications.



KJ-1170(External power)

Applications: Primary crushing, rocks applications and crushing

Maximum process capacity: 500 t/h
Hopper volume: 4 m³
Crusher unit: C106(1060mm*700mm)
Crusher unit power: 110 kW
Engine power: 97 kW/103 kW
Maximum feed size: 560 mm
Work dimension: 15600*7600*4800 mm
Transport dimension: 15500*3700*3800 mm
Total weight: 47 t



KJ-1170E(Dual power)

Applications: Primary crushing, rocks applications and crushing

Maximum process capacity: 500 t/h
Hopper volume: 5 m³
Crusher unit: C106(1060mm*700mm)
Crusher unit power: 110 kW
Generator power: 200 kW
Maximum feed size: 560 mm
Work dimension: 16500*3500*3800 mm
Transport dimension: 17500*3700*3800 mm
Total weight: 52 t



KJ-1170H(Diesel hydraulic)

Applications: Primary crushing, rocks applications and crushing

Maximum process capacity: 500 t/h
Hopper volume: 7 m³
Crusher unit: C106(1060mm*700mm)
Crusher unit drive: Hydraulic motor
Engine power: 310 kW
Maximum feed size: 560 mm
Work dimension: 16800*4400*4500 mm
Transport dimension: 15800*3166*3800 mm
Total weight: 53 t



KJ-1280(External power)

Applications: Primary crushing, rocks applications and crushing

Maximum process capacity: 520 t/h
Hopper volume: 6 m³
Crusher unit: C116(1150mm*760mm)
Crusher unit power: 132 kW
Engine power: 97 kW/103 kW
Maximum feed size: 610 mm
Work dimension: 17000*5400*4700 mm
Transport dimension: 17200*3800*3880 mm
Total weight: 55 t

※The output capacity varies depending on rock hardness, feed size, and discharge size. The technical parameters above are for reference only, and the actual specifications are subject to the delivered product.



KJ-1280E(Dual power)

Applications: Primary crushing, rocks applications and crushing

Maximum process capacity: 520 t/h
Hopper volume: 6 m³
Crusher unit: C116(1150mm*760mm)
Crusher unit power: 132 kW
Generator power: 250 kW
Maximum feed size: 610 mm
Work dimension: 17000*5400*4700 mm
Transport dimension: 17200*3800*3880 mm
Total weight: 58 t



KJ-1290(External power)

Applications: Large-scale operations in quarry and mining

Maximum process capacity: 610 t/h
Hopper volume: 8 m³
Crusher unit: C120(1200mm*870mm)
Crusher unit power: 160 kW
Engine power: 154 kW
Maximum feed size: 700 mm
Work dimension: 18200*4500*5100 mm
Transport dimension: 17600*3800*3900 mm
Total weight: 73.5 t



KJ-1290H(Diesel hydraulic)

Applications: Large-scale operations in quarry and mining

Maximum process capacity: 610 t/h
Hopper volume: 9 m³
Crusher unit: C120(1200mm*870mm)
Crusher unit drive: Hydraulic motor
Engine power: 310 kW
Maximum feed size: 700 mm
Work dimension: 21100*5700*5400 mm
Transport dimension: 18580*3400*3900 mm
Total weight: 75 t



※The output capacity varies depending on rock hardness, feed size, and discharge size. The technical parameters above are for reference only, and the actual specifications are subject to the delivered product.

KREAT
Impact series

Machines in this range include:

■ KI-1213RS / 1213ERS ■ KI-1214RS / 1214DRS / 1214E

KREAT KI series impact crushers are specially designed to meet customers' strict requirements for product quality. High performance and reliability can meet different crushing requirements and provide high-quality products with good shape, including manufactured sand, concrete manufacturing, and building solid waste recycling.



KI-1213RS(External power)

Applications: Demolition process, quarry and aggregate produce

Maximum process capacity: 360 t/h
Hopper volume: 5 m³
Crusher unit: CF250
Crusher unit power: 250 kW
Engine power: 97 kW
Maximum feed size: 500 mm
Work dimension: 17000*6620*4630 mm
Transport dimension: 17100*3760*3820 mm
Total weight: 54 t



KI-1213ERS(Dual power)

Applications: Demolition process, quarry and aggregate produce

Maximum process capacity: 360 t/h
Hopper volume: 7 m³
Crusher unit: CF250
Crusher unit power: 250 kW
Generator power: 400 kW
Maximum feed size: 500 mm
Work dimension: 19600*6600*4100 mm
Transport dimension: 17600*3760*3830 mm
Total weight: 66 t



KI-1214RS(External power)

Applications: Demolition process, quarry and aggregate produce

Maximum process capacity: 400 t/h
Hopper volume: 7 m³
Crusher unit: KI-130
Crusher unit power: 250 kW
Engine power: 133 kW
Maximum feed size: 600 mm
Work dimension: 21300*7300*5600 mm
Transport dimension: 20300*3800*3850 mm
Total weight: 69 t



KI-1214E(Dual power)

Applications: Demolition process, quarry and aggregate produce

Maximum process capacity: 400 t/h
Hopper volume: 7 m³
Crusher unit: KI-130
Crusher unit power: 250 kW
Engine power: 400 kW
Maximum feed size: 600 mm
Work dimension: 17500*3900*4600 mm
Transport dimension: 17800*3600*3850 mm
Total weight: 57.8 t



KI-1214DRS(Direct drive)

Applications: Demolition process, quarry and aggregate produce

Maximum process capacity: 400 t/h
Hopper volume: 7 m³
Crusher unit: KI-130
Crusher unit power: 250 kW
Engine power: 364 kW
Maximum feed size: 600 mm
Work dimension: 21300*7300*5750 mm
Transport dimension: 20300*3800*3850 mm
Total weight: 72 t

※The output capacity varies depending on rock hardness, feed size, and discharge size. The technical parameters above are for reference only, and the actual specifications are subject to the delivered product.

KREAT
Cone series

Machines in this range include:

■ KC-440RS / 440ERS ■ KC-300RS / 300ERS / 300HRS ■ KC-400RS

KREAT KC series cone crushers use attrition to crush materials for the production of a cubical end product. They are ideally suited to secondary, tertiary or quaternary applications.



KC-440RS(External power)

Applications: Aggregate produce, primitive rock, river gravel, secondary and tertiary crush

Maximum process capacity: 350 t/h
Hopper volume: 3 m³
Crusher unit: CC440
Crusher unit power: 250 kW
Engine power: 97 kW/103 kW
Maximum feed size: 215 mm
Work dimension: 18700*4500*5200 mm
Transport dimension: 19350*3830*3850 mm
Total weight: 52 t



KC-440ERS(Dual power)

Applications: Aggregate produce, primitive rock, river gravel, secondary and tertiary crush

Maximum process capacity: 350 t/h
Hopper volume: 3 m³
Crusher unit: CC440
Crusher unit power: 250 kW
Generator power: 536 kW
Maximum feed size: 215 mm
Work dimension: 18700*4500*5200 mm
Transport dimension: 19350*3830*3850 mm
Total weight: 56 t



KC-300RS(External power)

Applications: Aggregate produce, primitive rock, river gravel, secondary and tertiary crush

Maximum process capacity: 380 t/h
Hopper volume: 3 m³
Crusher unit: AGP300
Crusher unit power: 250 kW
Engine power: 97 kW/103 kW
Maximum feed size: 215 mm
Work dimension: 18700*4500*5200 mm
Transport dimension: 19350*3830*3850 mm
Total weight: 52 t



KC-300ERS(Dual power)

Applications: Aggregate produce, primitive rock, river gravel, secondary and tertiary crush

Maximum process capacity: 380 t/h
Hopper volume: 3 m³
Crusher unit: AGP300
Crusher unit power: 250 kW
Generator power: 536 kW
Maximum feed size: 215 mm
Work dimension: 18700*4500*5200 mm
Transport dimension: 19350*3830*3850 mm
Total weight: 56 t



KC-300HRS(Diesel hydraulic)

Applications: Aggregate produce, primitive rock, river gravel, secondary and tertiary crush

Maximum process capacity: 380 t/h
Hopper volume: 5 m³
Crusher unit: AGP300
Crusher unit drive: Hydraulic drive
Engine power: 400 kW
Maximum feed size: 215 mm
Work dimension: 19700*10700*5300 mm
Transport dimension: 20200*3800*3800 mm
Total weight: 65 t



KC-400RS(External power)

Applications: Aggregate produce, primitive rock, river gravel, secondary and tertiary crush

Maximum process capacity: 500 t/h
Hopper volume: 3 m³
Crusher unit: AGP400
Crusher unit power: 315 kW
Engine power: 133 kW
Maximum feed size: 250 mm
Work dimension: 19000*4900*6000 mm
Transport dimension: 18400*3830*3850 mm
Total weight: 73 t

※The output capacity varies depending on rock hardness, feed size, and discharge size. The technical parameters above are for reference only, and the actual specifications are subject to the delivered product.

KREAT
VSI series

Machines in this range include:

■ KPV-7150RS ■ KPR-320RS

KREAT KP Series mobile sand making machine is widely used in the aggregate, construction, and road industries. It is capable of processing materials such as river pebble, granite, limestone, and basalt.



KPV-7150RS(External power)

Applications: shaping and fine material aggregate produce

Maximum process capacity: 180-280 t/h
Hopper volume: 1 m³
Crusher unit: VSI1032
Crusher unit power: 320 kW
Engine power: 97 kW
Maximum feed size: 40 mm
Work dimension: 18700*4800*5600 mm
Transport dimension: 20000*3800*3800 mm
Total weight: 47 t



KPR-320RS(External power)

Applications: Middle hardness material crushing, adjustable fine material produce with high efficiency

Maximum process capacity: 140-200 t/h
Hopper volume: 3 m³
Crusher unit: G90x60C
Crusher unit power: 320 kW
Engine power: 133 kW
Maximum feed size: 35 mm
Work dimension: 20400*4300*5900 mm
Transport dimension: 20800*3900*3800 mm
Total weight: 68 t



※The output capacity varies depending on rock hardness, feed size, and discharge size. The technical parameters above are for reference only, and the actual specifications are subject to the delivered product.

KREAT
Screen series

Machines in this range include:

■ KS-133 / 133E ■ KS-933H

The KREAT KS series mobile inclined screeners are designed for the processing of aggregates and sand. All KS machines are designed to be easily transported, set-up, operated and maintained.



KS-133(External power)

Applications: Aggregate, primitive rock, demolition aggregate screening

Maximum process capacity: 350 t/h
Hopper volume: 2.3 m³
Screen box dimension: 6500*2000 mm
Screen box decks: 3
Engine power: 97 kW
Maximum stacking height: 3750 mm
Work dimension: 14200*12100*6800 mm
Transport dimension: 14700*3600*3820 mm
Total weight: 33 t



KS-133E(Dual power)

Applications: Aggregate, primitive rock, demolition aggregate screening

Maximum process capacity: 350 t/h
Hopper volume: 2.3 m³
Screen box dimension: 6500*2000 mm
Screen box decks: 3
Generator power: 100 kW
Maximum stacking height: 3750 mm
Work dimension: 14700*15730*7100 mm
Transport dimension: 16400*3780*3830 mm
Total weight: 32 t



KS-933H(Diesel hydraulic)

Applications: Aggregate, primitive rock, demolition aggregate screening

Maximum process capacity: 320 t/h
Hopper volume: 8 m³
Screen box dimension: 7200*1565 mm
Screen box decks: 3
Engine power: 93 kW
Maximum stacking height: 4400 mm
Work dimension: 20100*19700*6600 mm
Transport dimension: 19900*3350*3800 mm
Total weight: 42 t



※The output capacity varies depending on rock hardness, feed size, and discharge size. The technical parameters above are for reference only, and the actual specifications are subject to the delivered product.

KREAT
Screen series

Machines in this range include:

■ KSH-6203 / 6203HR

KREAT KSH series mobile horizontal screen is an ideal choice for screening sand and gravel aggregates. It is suitable for processing both natural aggregates and crushed aggregates.



KSH-6203(External power)

Applications: Aggregate, primitive rock screening

Maximum process capacity: 500 t/h
Hopper volume: 0.8 m³
Screen box dimension: 6100*1930 mm
Screen box decks: 3
Engine power: 93 kW
Maximum stacking height: 3200 mm
Work dimension: 20400*14900*5340 mm
Transport dimension: 19200*3640*3950 mm
Total weight: 38 t



KSH-6203HR(Diesel hydraulic)

Applications: Aggregate, primitive rock screening

Maximum process capacity: 500 t/h
Hopper volume: 5 m³
Screen box dimension: 6100*1930 mm
Screen box decks: 3
Engine power: 168 kW
Maximum stacking height: 5300 mm
Work dimension: 25000*16200*4600 mm
Transport dimension: 21800*3200*3900 mm
Total weight: 51.5 t



※The output capacity varies depending on rock hardness, feed size, and discharge size. The technical parameters above are for reference only, and the actual specifications are subject to the delivered product.

KREAT
Scalping screen series

Machines in this range include:

■ KSZ-500H ■ KSZ-600H ■ KSZ-800E

KREAT KSZ series mobile scalping screens are high capacity, heavy duty, versatile machines capable of screening and separating a wide variety of material in the most difficult and demanding of applications, including recycling, aggregates, compost, topsoil, coal, construction and demolition waste, and iron ore.



KSZ-500H(Diesel hydraulic)

Applications: Coarse material pre-screening, fine aggregates, wet and sticky material screening

Maximum passing capacity: 500 t/h
Hopper volume: 6 m³
Screen box dimension: 3470*1395 mm
Screen box decks: 2
Engine power: 93 kW
Maximum stacking height: 3650 mm
Work dimension: 14800*12700*3850 mm
Transport dimension: 13500*3100*3550 mm
Total weight: 30 t



KSZ-600H(Diesel hydraulic)

Applications: Coarse material pre-screening, fine aggregates, wet and sticky material screening

Maximum passing capacity: 600 t/h
Hopper volume: 6 m³
Screen box dimension: 5000*1550 mm
Screen box decks: 2
Engine power: 93 kW
Maximum stacking height: 3650 mm
Work dimension: 14800*12800*4900 mm
Transport dimension: 14800*3600*3850 mm
Total weight: 35 t



KSZ-800E(Dual power)

Applications: Coarse material pre-screening, fine aggregates, wet and sticky material screening

Maximum passing capacity: 800 t/h
Hopper volume: 10 m³
Screen box dimension: 6100*1830 mm
Screen box decks: 2
Generator power: 150 kW
Maximum stacking height: 4050 mm
Work dimension: 18300*16000*5100 mm
Transport dimension: 18700*3700*3800 mm
Total weight: 46 t



※The output capacity varies depending on rock hardness, feed size, and discharge size. The technical parameters above are for reference only, and the actual specifications are subject to the delivered product.

KREAT
Auxiliary series

Machines in this range include:

■ KMC-1023H ■ KXT-120M ■ KDU-75M

KMC Series mobile conveyor can increase the stacking height of materials.
KXT Series washing and screening integrated machine is specifically designed for fine sand washing and dewatering.
KDU Series M-Sand Classifier is a specialized equipment designed for the removal of excess fines from manufactured sand, enabling the powder content within the sand to be adjustable and controllable.



KMC-1023H (Diesel hydraulic)

Applications: Increase stacking height

Maximum processing capacity: 500 t/h
Maximum feed size: 300 mm
Conveyor belt width: 1000 mm
Maximum stacking height: 8500 mm
Engine power: 45 kW
Work dimension: 21500*2400*9500 mm
Transport dimension: 12000*2400*2600 mm
Drive type: Hydraulic
Total weight: 15 t



KXT-120M (External power)

Applications: Concrete, mortar and asphalt sand, solid waste recycling material processing, stone powder sand washing, river sand washing, sea sand washing, quartz sand washing, glass manufacturing, iron ore washing and Gobi desert sand washing.

Bucket wheel diameter: 2600 mm
Bucket wheel width: 750 mm-Double row
Bucket wheel speed: 1.2-1.8 rpm
Dewatering screen dimension: 3700*1500 mm
Slurry pump power: 30 kW
Total weight: 15.8 t
Processing capacity: 80-120 t/h
Work dimension: 8600*4400*5000 mm
Transport dimension: 8600*3800*3800 mm
Working power: 55 kW



KDU-75M (External power)

Applicable to: concrete, mortar, and asphalt sand; stone powder washing for recycled solid-waste materials; river sand and sea sand washing; quartz sand; the glass manufacturing industry; iron ore; and sand washing in the Gobi Desert.

Powder control percentage: 3-10%
Powder storage tank volume: 6 m^3
Treatment capacity of the agitated humidifier: 80-100 t/h
Maximum stacking height: 2910 mm
Air compressor displacement: 2.6 m3/min
Air compressor power: 15 kW
Total weight: 25.5 t
Processing capacity: 0-100 t/h
Transport dimension: 11300*3950*3870 mm
Working power: 137 kW



※The output capacity varies depending on rock hardness, feed size, and discharge size. The technical parameters above are for reference only, and the actual specifications are subject to the delivered product.



KREAT
Modular series

Machines in this range include:

■ KJ-1170M / 1280M / 1290M ■ KI-1213MRS ■ KC-300MRS / 400MRS / 440MRS ■ KS-133M

KREAT modular series is designed to efficiently address primary, secondary, tertiary, or quaternary crushing applications in the mining, quarrying, concrete aggregates, and construction waste recycling industries, meeting the crushing and screening demands for fine processing.



KJ-1170M (External power)

Applications: Primary crushing, rocks applications and crushing

Maximum process capacity: 500 t/h
Hopper volume: 4 m³
Crusher unit: C106(1060mm*700mm)
Crusher unit power: 110 kW
Maximum feed size: 560 mm
Work dimension: 15600*3400*4400 mm
Transport dimension: 15500*3340*3750 mm
Working power: 138 kW
Total weight: 36.3 t



KJ-1280M (External power)

Applications: Primary crushing, rocks applications and crushing

Maximum process capacity: 520 t/h
Hopper volume: 5 m³
Crusher unit: C116(1150mm*760mm)
Crusher unit power: 132 kW
Maximum feed size: 610 mm
Work dimension: 17000*5400*4500 mm
Transport dimension: 17000*3400*3800 mm
Working power: 168 kW
Total weight: 45 t



KI-1213MRS (External power)

Applications: Demolition process, quarry and aggregate produce

Maximum process capacity: 360 t/h
Hopper volume: 5 m³
Crusher unit: CF250
Crusher unit power: 250 kW
Maximum feed size: 500 mm
Work dimension: 18600*5000*5200 mm
Transport dimension: 17200*3800*3800 mm
Working power: 310 kW
Total weight: 54 t



KC-440MRS (External power)

Applications: Aggregate produce, primitive rock, river gravel, secondary and tertiary crush

Maximum process capacity: 350 t/h
Hopper volume: 1 m³
Crusher unit: CC440
Crusher unit power: 250 kW
Maximum feed size: 215 mm
Work dimension: 17500*3820*5100 mm
Transport dimension: 18500*3820*3800 mm
Working power: 316.3 kW
Total weight: 37 t



KC-300MRS (External power)

Applications: Aggregate produce, primitive rock, river gravel, secondary and tertiary crush

Maximum process capacity: 380 t/h
Hopper volume: 1 m³
Crusher unit: AGP300
Crusher unit power: 250 kW
Maximum feed size: 215 mm
Work dimension: 17500*3820*5100 mm
Transport dimension: 18500*3820*3800 mm
Working power: 316.3 kW
Total weight: 38 t



KS-133M (External power)

Applications: Aggregate, primitive rock, demolition aggregate screening

Maximum process capacity: 350 t/h
Hopper volume: 0.7 m³
Screen box dimension: 6500*2000 mm
Screen box decks: 3
Maximum stacking height: 3400 mm
Work dimension: 14200*12200*5800 mm
Transport dimension: 14700*3670*3600 mm
Working power: 62.5 kW
Total weight: 26 t

※The output capacity varies depending on rock hardness, feed size, and discharge size. The technical parameters above are for reference only, and the actual specifications are subject to the delivered product.

NOTES

www.kreatgroup.com

MASTER THE CORE
STABILITY TECHNOLOGY