

- Retractable undercarriage, robot welding, and welding seam forming completely eliminate the influence of human factors, the arc is stable, the penetration depth is controllable, and the forming is beautiful.
- The crushing pipeline is standard, and various attachments such as hammers, rippers, grabbers, augers, etc. can be added, and one machine can be used for multiple purposes.

DIG-DOG DG10 MINI EXCAVATOR

Adress: B7,Yunchuang Technology Park,Xuzhou,China 221000

♣ Phone:+86-516 8753 3040

Email: sales@dig-dog.com

Website: www.DIG-DOG.com



MAIN SPECIFICATIONS

Machine model No.		DG10
Type of tracks		Rubber track
Operating weight		1000kg
Bucket Capacity		0.025m ³ /380mm width
System Pressure		16Mpa
Max. grade ability		35°
Max.Bucket Digging Force		7.2KN
Max.Arm Digging Force		4.6KN
Operation type		Joystick poilt control
Engine	Model	KOOP KD192F
	Displacement	1.532L
	Туре	Single -cylinder wind -cold engine
	Max. Power	7kW/3000r/min
Overall Dimensions	Overall Length	2840mm
	Overall Width	880mm
	Overall height	2220mm
	Chassis width	840mm
	Min. ground clearance	132mm
	Cabin height	2220mm
	Axle base	900mm
Dimensio ns.	Width.	720mm
	Driver height.	2030mm
	Seat height.	1300mm
	Length.	2600mm
working range	Max.Digging Height	2600mm
	Max.Dumping Height	1830mm
	Max.Digging Depth	1715mm
	Max.Vertical Digging Depth	1590mm
	Max.Digging Radius	3065mm
	Min.Swing Radius	1480mm

MAIN DIMENSIONS





