



TUBOMATIC H130 ES

Code: **TUBH130ES**

CRIMPING (STANDARD VOLUME CRIMPING)
扣压机 (标准产量型)



TUBOMATIC H130 EL

Code: **TUBH130ELC**

CRIMPING (STANDARD VOLUME CRIMPING)
扣压机 (标准产量型)



TUBOMATIC H130/E EL

Code: **TUBH130/EEL**

CRIMPING (STANDARD VOLUME CRIMPING)
扣压机 (标准产量型)



ALSO AVAILABLE WITH
PORTABLE DIES HOLDER
可提供便携
发散式模具柜

MAIN FEATURES - 主要特点



Ideal for any type of fitting

可扣压各种形式
胶管接头



ES3 touch-screen
electronic control

ES3数控触摸屏

H130 ES



Back limit switch

后接触式扣压装置

H130 ES



Electro-mechanical
control

电动控制面板

**H130 EL
H130/E EL**



Warning LED

LED报警提示

H130 EL



Vernier dial

游标刻度盘

**H130 EL
H130/E EL**



Ideal for your workshop

车间的理想选择

TECHNICAL DATA - 技术参数			
	H130 ES	H130 EL	H130/E EL
CRIMPING FORCE 扣压力	190 TON	190 TON	250 TON
6 SPIRALS 2 PIECES 6层	1" 1/4	1" 1/4	1" 1/4
4 SP 2 PIECES 4层	2"	2"	2"
INDUSTRIAL HOSE 工业管	3"	3"	3"
MAX Ø 扣压后最大尺寸	130 mm [♦]	124 mm [♦]	111 mm [♦]
CRIMPING / HOUR 扣压次数/小时	780 [■]	780 [■]	246 [■]
DIE OPENING 模具张开量	Ø + 35 mm	Ø + 35 mm	Ø + 35 mm
90° FITTINGS 90° 胶管接头	2"	2"	2"
STANDARD VOLTAGE 标准电压	375V-420V 50HZ 3PH	375V-420V 50HZ 3PH	375V-420V 50HZ 3PH
MOTOR POWER 电机功率	4 Kw (5.5 Hp)	4 Kw (5.5 Hp)	2.2 Kw (2.9 Hp)
DIMENSIONS LxWxH 尺寸 长x宽x高	760x690x730 mm	760x675x715 mm	668x588x661 mm
WEIGHT WITHOUT OIL 净重 (不含油)	295 Kg	295 Kg	206 Kg
OIL (NOT INCLUDED) 液压油 (不包含)	65 Lt.	65 Lt.	22 Lt.
SETTABLE RE-OPENING TIME AFTER CRIMPING 设置张开量	-	■	-
SETTABLE CRIMPING TIME 设置保压时间	-	■	-

ACCESSORIES - 附件 (可选配)				
		H130 ES	H130 EL	H130/E EL
PRESSURE CONTROL SYSTEM KIT 压力控制系统		■	-	-
USB KIT USB 接口		■	-	-
QUALITY CHECK: PRESSURE AND DIAMETER COMBINED CONTROL 质量检测系统: 压力与尺寸配合控制		■	-	-
MULTISTEP CRIMPING DIAMETERS 多尺寸设定系统		■	-	-
DISPENSER + PATENTED QUICK CHANGE TOOL 发散式模具柜 + 专利的快速切换工具		■	■	■
BASE 底座		■	■	■
BACK MIRROR 后视镜		■	■	-
CLEANING AND MAINTENANCE KIT 清洗保养套装		■	■	■
ELECTRIC PEDAL 脚踏板		■	■	■

Diameter (mm) 模具尺寸 (mm)	10	12	14	16	19	22	25	29	34	38	42	46	50	54	58	63	69	73
	DIES LENGTH (mm) / 模具长度 (mm)																	
H130 ES H130 EL - H130/E EL	60	60	60	60	60	60	60	70	70	85	85	95	95	95	95	100	100	100

■ THEORETICAL WITH 1/2" Δ Ø 6 MM HOSE - ♦ WITH SPECIAL DIES Ø 104 MM UPON REQUEST

■ 1/2" Δ Ø 6 MM软管为理论数据 - ♦ 根据需求可提供特制模具Ø104MM

ALL CAPACITIES INDICATED DEPEND ON THE KIND OF FITTING USED - 所有标注的加工范围取决于所使用的接头类型

Product specifications could be modified without prior notice.
产品说明如有更改, 恕不另行通知。