

烟台春晖回转支承挖机参数表

编号	滚道中心直径	外径	内径	总高	齿数	模数	压力角
403	280	384	200	60	94	4	20°
352	400	458	324.8	40.5	110	3	20°
248	400	458	320	41	82	4	20°
348	400	459.4	320.6	40.5	82	4	20°
350	400	461	320.7	36	82	4	20°
257	400	465	319	37	73	4.5	20°
349	400	458	320	35	73	4.5	20°
353	400	458	320	35	73	4.5	20°
351	400	458	319.5	37	73	4.5	20°
300	420	510	323.2	60	82	4	20°
249	437	499	356	40	81	4.5	20°
390	437	498	350	40	71	5	20°
323	450	543	336	60	85	4	20°
281	465	535	380	42.5	96	4	20°
301	465	545	380	55	96	4	20°
358	480	573	380	55	96	4	20°
302	480	570	380	55	96	4	20°
375	480	546	380.5	46	77	5	20°
411	523	585	439	47	100	4.5	20°
334	528	604	431	47	88	5	20°
250	528	599	429	50	80	5.5	20°
398	529	594	441	53	89	5	20°
286	544	614.5	452	53.5	92	5	20°
214	567	640	473	55	96	5	20°
272	567	640	473	55	96	5	20°
304	567	640	471.6	60	80	6	20°
287	568	640	471.5	55	96	5	20°
259	568	645	468	55	80	6	20°
213	569	640	471	55	80	6	20°
370	586	665	474	62	80	6	20°
409	586	665	474	62	80	6	20°
211	600	685	483	60	82	6	20°
364	603	678	500.5	60	79	6.5	20°
363	603	678	501.5	60	79	6.5	20°
140	608	694	494	60	78	6.5	20°
142	608	694	495	60	78	6.5	20°
362	634	732	494.4	60	83	6	20°
94	634	732	494.4	65	83	6	20°
149	650	744	514	60	74	7	20°
96	674	750	573	60	90	6.5	20°
157	675	748	573	60	90	6.5	20°
159	680	755	574	67	90	6.5	20°
314	682	774	555	80	81	7	20°
197	683	765	562	97	71	8	20°
285	683	766	560	97	71	8	20°
52	683	774	554	78	71	8	20°
53	686	781	554	78	71	8	20°
405	689	771	576.1	62	84	7	20°
155	692	770	575	73	84	7	20°

烟台春晖回转支承控机参数表

编号	滚道中心直径	外径	内径	总高	齿数	模数	压力角
347	693	795	554	81	71	8	20°
193	696	806	545	84	70	8	20°
206	710	806	584	70	98	6	20°
223	710	806	552	70	93	6	20°
376	710	806	584	80	98	6	20°
150	710	810	572	80	96	6	20°
356	710	804	582	70	84	7	20°
205	710	804	582	70	84	7	20°
79	715	800	573	70	90	6.5	20°
40	715	800	590	74	86	7	20°
167	715	800	590	70	86	7	20°
152	715	800	590	70	86	7	20°
207	715	800	590	70	86	7	20°
269	715	800	590	70	86	7	20°
240	715	800	590	74	86	7	20°
37	720	806	596	74	76	8	20°
104	720	810	584	84	75	8	20°
244	720	810	585	83	75	8	20°
95	720	810	586	84	75	8	20°
289	720	810	584	85	75	8	20°
80	720	810	585	84	75	8	20°
186	720	811	586	84	75	8	20°
382	720	810	586	84	75	8	20
93	720	810	586	83	75	8	20°
108	720	806	593	73	76	8	20°
263	730	811	616	75	90	7	20°
332	730	811	616	65	90	7	20°
92	730	810	621	75	90	7	20°
261	730	811	616	75	90	7	20°
35	730	812	616	75	90	7	20°
127	730	811	616	75	90	7	20
209	730	811	621	75	90	7	20°
210	730	811	621	75	90	7	20°
168	730	811	601	75	76	8	20°
346	746	844	616	75	90	7	20°
384	756	833	649	64	110	6	20°
385	760	845	648	66	110	6	20°
241	760	845	648	58	110	6	20°
141	760	845	616	70	89	7	20°
139	760	850	637	75	93	7	20°
54	760	852	629	75	80	8	20°
36	760	852	627	74	80	8	20
321	760	854	625	75	79	8	20°
202	760	852	627	74	80	8	20°
294	760	852	627	75	80	8	20°
228	760	852	627	75	80	8	20°
386	764	852	648.5	70	109	6	20°
412	781	871	641	85	82	8	20°
293	783	868	652	75	82	8	20°

烟台春晖回转支承控机参数表

编号	滚道中心直径	外径	内径	总高	齿数	模数	压力角
74	795	902	640	82	82	8	20°
19	795	900	640	83	82	8	20°
212	800	908	651	86	94	7	20°
276	800	922	635.2	78	80	8	20°
369	800	922	635.2	78	80	8	20°
262	800	922	635.2	100	80	8	20°
187	800	895	664	68	84	8	20°
230	800	896	664	78	84	8	20°
57	800	922	635	107	80	8	20°
260	800	896	665.9	68	84	8	20°
367	800	909	648	78	82	8	20°
344	800	909	647	78	82	8	20°
237	800	895	666	78	84	8	20
97	800	895	664	68	84	8	20
145	800	908	648	78	82	8	20°
238	800	895	664	68	84	8	20
239	800	895	664	68	84	8	20
337	800	896	664	75	84	8	20
397	800	908	648	78	82	8	20°
299	800	913	649.5	85	82	8	20°
87	808	900	665	85	85	8	20°
224	850	981	682	80	86	8	20°
328	862	952	736	69	94	8	20°
234	900	973	785	92	100	8	20°
231	900	1008	744	78	94	8	20°
401	900	993	764	80	78	10	20°
147	908	990	785	73	100	8	20°
330	910	1000	785.6	85	100	8	20°
151	985	1098	822	90	83	10	20°
143	995	1090	860	86	88	10	27°
41	996	1092	862	84	88	10	20°
180	1000	1122	824	100	83	10	20°
182	1000	1122	819	100	83	10	20°
183	1000	1122	819	100	83	10	20°
247	1000	1122	824	100	83	10	20°
253	1007	1116	878	105	89	10	20°
387	1007	1116	878	105	89	10	20°
311	1010	1093	889	87	112	8	20°
325	1010	1113	871	96	89	10	20°
246	1010	1120	850	78	86	10	20°
343	1010	1120	852	76	86	10	20°
338	1015	1115	883	75	90	10	27°
264	1017	1093	872	90	89	10	20°
265	1017	1093	872	90	89	10	20°
331	1020	1120	882	93	90	10	20°
345	1040	1146	887	80	90	10	20°
275	1045	1132	923	85	93	10	20°
309	1045	1132	923	85	93	10	20°
270	1060	1180	889	90	90	10	20°

烟台春晖回转支承挖机参数表

编号	滚道中心直径	外径	内径	总高	齿数	模数	压力角
333	1076	1163	961	94	98	10	20°
282	1082	1189	922	83	94	10	20°
188	1085	1169	973	85	98	10	20°
360	1085	1170	972.5	88	98	10	25°
199	1085	1215	940	115	94	10	20°
295	1088	1172	972	88	98	10	25°
365	1100	1195	962	85	98	10	20°
273	1100	1195	941	102	80	12	20°
274	1100	1197	939	98	80	12	20°
415	1100	1200	945	100	80	12	20°
222	1102	1195	963	85	98	10	20°
225	1102	1195	967	85	98	10	20°
245	1103	1195	963	90	98	10	20°
184	1103	1200	947	81	80	12	20°
392	1103	1201	946	80	80	12	20°
175	1110	1224	973	82	99	10	27°
359	1110	1215	960	85	98	10	20°
402	1110	1215	960	85	98	10	20°
233	1120	1244	940	90	95	10	20°
377	1120	1229	971	85	99	10	20°
235	1120	1242	944	100	95	10	20°
229	1185	1310	1042	95	104	10	27°
291	1200	1365	1008	150	84	12	20°
23	1203	1302	1084	109.5	110	10	27°
22	1203	1303	1084	104	110	10	27°
72	1203	1323	1084	100	110	10	27°
71	1203	1323	1084	100	110	10	27°
383	1203	1323	1084	100	110	10	27°
195	1203	1323	1083	100	110	10	27°
354	1203	1316	1084	105	110	10	27°
45	1203	1322	1078	100	96	11.5	27°
413	1203	1322	1078.4	113	96	11.5	27°
194	1203	1323	1073	112	92	12	27°
24	1203	1322	1070	113	92	12	27°
77	1203	1322	1071	100	91	12	20°
89	1203	1322	1071	100	91	12	20°
255	1203	1322	1071	100	91	12	20°
110	1203	1322	1071	99.5	91	12	20°
298	1204	1323	1071	104	92	12	20°
198	1211	1309	1082	108	110	10	25°
266	1212	1300	1080	110	92	12	20°
267	1212	1310	1056	105	90	12	20°
2	1213	1309	1082	108	110	10	25°
268	1217	1315	1083	99	92	12	20°
190	1220	1310	1083	110	92	12	20°
191	1220	1301	1084	110	92	12	20°
242	1220	1327	1084	110	92	12	20°
232	1220	1328	1084	100	92	12	20°
357	1220	1327	1083	110	92	12	27°

烟台春晖回转支承挖机参数表

编号	滚道中心直径	外径	内径	总高	齿数	模数	压力角
335	1220	1327	1083	110	92	12	20°
200	1220	1365	1016	120	86	12	20°
236	1220	1365	1035	105	87	12	20°
227	1220	1327	1083	110	92	12	20°
393	1220	1327	1071	99.5	91	12	20
226	1220	1340	1083	110	92	12	20°
312	1227	1328	1094	102	92	12	25°
254	1230	1344	1071	110	91	12	20°
216	1240	1358	1080	100	91	12	20°
416	1240	1358	1084.8	100	91	12	20°
388	1250	1400	1017	120	86	12	20°
317	1250	1370	1032	105	88	12	20°
204	1250	1370	1032	102	88	12	20°
324	1250	1370	1085	110	92	12	20°
217	1250	1370	1034	105	88	12	20°
303	1250	1400	1018	120	86	12	20°
310	1250	1390	1047.43	110	88	12	20°
258	1250	1387	1085	130	92	12	20°
201	1250	1390	1048	110	88	12	20°
38	1260	1375	1094	121	92	12	27°
306	1265	1388	1080	105	91	12	20°
283	1265	1388	1080	105	91	12	20°
288	1295	1410	1083	116	110	10	27°
320	1295	1408	1131	121	82	14	20°
307	1295	1410	1132	120	82	14	20°
315	1295	1410	1131	117	82	14	20°
33	1297	1418	1131	120	82	14	20°
326	1300	1416	1140	109	97	12	27°
292	1308	1480	1116	145	93	12	20°
189	1315	1430	1157	100	97	12	20°
339	1320	1443.5	1156	110	97	12	20°
318	1321	1444	1156	110	97	12	20°
120	1325	1460	1144	122	96	12	20°
164	1330	1459	1164	110	85	14	20°
290	1340	1475	1165	120	85	14	27°
410	1340	1464	1192.8	135	86	14	20°
165	1350	1495	1164	110	85	14	20°
361	1350	1494	1164	120	85	14	20°
284	1362	1510	1193	135	86	14	20°
313	1400	1540	1195.6	110	86	14	20°
408	1403	1526	1235	122	90	14	27°
336	1404	1532	1235	124	90	14	27°
417	1405	1532	1235	125	90	14	20°
319	1405	1550	1235	140	90	14	20°
327	1405	1527	1235	122	90	14	20°
389	1405	1536	1236	125	90	14	20°
119	1405	1532	1235	122	90	14	27°
271	1405	1526	1235	130	90	14	27°
218	1405	1536	1236	125	90	14	20°

烟台春晖回转支承挖机参数表

编号	滚道中心直径	外径	内径	总高	齿数	模数	压力角
256	1405	1550	1235	140	90	14	20°
277	1405	1535	1234.8	122	89	14	20°
297	1405	1530	1236	122.5	90	14	20°
366	1405	1550	1237	140	90	14	20°
196	1405	1550	1238	152	84	15	27°
406	1405	1563	1238.4	152	78	16	20°
124	1407	1552	1236	132	90	14	27°
278	1412	1581	1238	160	84	15	27°
121	1433	1584	1235	132	90	14	27°
208	1435	1589	1219	120	88	14	20°
243	1435	1595	1218	120	88	14	20°
123	1435	1595	1218		88	14	20°
280	1446	1590	1200	120	77	16	20°
169	1456	1615	1275	145	92	14	27°
192	1470	1596	1278	110	92	14	20°
296	1470	1605	1271.2	120	92	14	20°
215	1510	1665	1312	138	84	16	20°
380	1515	1654	1316	122	95	14	20°
340	1520	1665	1313.5	135	84	16	20°
305	1522	1630	1346	116	98	14	20°
219	1524	1656	1348	125	97	14	20°
404	1524	1656	1348	127	97	14	20°
355	1530	1675	1328	132	84	16	20°
374	1530	1675	1328	132	84	16	20°
407	1530	1675	1331	142	84	16	20°
126	1530	1680	1315	152	83	16	20
125	1530	1680	1331	152	84	16	20
221	1530	1680	1315	152	83	16	20
170	1542	1691	1313	130	84	16	27°
251	1556	1710	1344	142	85	16	20°
371	1556	1710	1344	142	85	16	20°
381	1556	1710	1344	142	85	16	20°
373	1612	1793	1360	190	87	16	20°
378	1622	1748	1429.4	120	101	14	20°
379	1622	1748	1429.4	120	101	14	20°
308	1634	1815	1374	182	100	14	27°
414	1676	1855	1430.4	160	90	16	20°
341	1676	1845	1430	160	90	16	20°
279	1680	1854	1441	140	104	14	20°
220	1680	1817	1474	121	93	16	20°
316	1701	1864	1460	178	92	16	20°
166	1750	1950	1457	215	93	16	20°
252	1765	1928	1524	178	96	16	20°
368	1778	1990	1430.4	210	90	16	20°
372	1815	2020	1524	194	96	16	20°
185	1860	2037	1595	160	115	14	20°
399	1860	2037	1595	160	115	14	20°
203	2233	2435	1955	237	132	15	20°
394	2700	2945	2320	220	131	18	20°

烟台春晖回转支承控机参数表

编号	滚道中心直径	外径	内径	总高	齿数	模数	压力角
181	1000	1122	818	100	83	10	20°
109	1000	1122	824	100	83	10	20°
81	1005	1095	863	80	88	10	20°
78	1007	1093	880	85	89	10	20°
84	1010	1093	882	72.5	90	10	27°
342	1010	1093	882	72.5	90	10	27°
50	1012	1106	884	77	90	10	20°
173	1012	1106	884	77	90	10	20°
75	1014	1115	882	75	90	10	27°
66	1020	1110	882	77	90	10	20°
99	1020	1111	873	75	89	10	20°
88	1020	1111	873	75	89	10	20°
98	1020	1133	861	90	88	10	27°
6	1087	1171	973	80	98	10	27°
55	1087	1171	973	88	98	10	27°
176	1087	1172	973	87	98	10	27°
20	1094	1209	916	95	78	12	20°
178	1095	1205	962.2	94	98	10	25°
59	1100	1195	962	86	98	10	20°
63	1100	1195	964	85	98	10	20°
65	1100	1202	947	83	80	12	20°
90	1103	1195	963	85	98	10	20°
31	1200	1307	1084	100	110	10	27°
9	1200	1323	1084	99	110	10	27°
69	1200	1316	1084	100	110	10	27°
67	1200	1316	1084	105	110	10	27°
29	1201	1316	1084	105	110	10	27°
21	1210	1311	1084	105	110	10	27°
17	1210	1310	1082	105	110	10	27°
3	1210	1311	1084	105	110	10	27°
16	1212	1310	1084	106	92	12	20°
10	1212	1310	1084	106	92	12	27°
18	1212	1316	1084	96	92	12	27°
25	1212	1310	1084	110	79	14	20°
51	1213	1320	1084	95	92	12	20°
28	1220	1328	1084	111	92	12	20°
12	1220	1327	1084	111	92	12	27°
61	1220	1327	1084	110	92	12	20°
62	1220	1327	1083	108	92	12	20°
1	1220	1327	1084	110	92	12	27°
73	1220	1327	1071	99.5	91	12	20°
146	1220	1328	1084	110	92	12	20°
329	1220	1327	1083	111	92	12	20°
154	1220	1327	1083	110	92	12	20°
39	1227	1330	1093	102	92	12	27°
47	1227	1330	1093	102	92	12	25°
48	1227	1330	1093	102	92	12	27°
76	1227	1328	1094	102	92	12	25°
56	1228	1330	1093	103	92	12	25°

烟台春晖回转支承控机参数表

编号	滚道中心直径	外径	内径	总高	齿数	模数	压力角
177	1240	1361	1080	105	91	12	20°
32	1240	1358	1080	100	91	12	20°
64	1240	1356	1080		91	12	20°
60	1250	1370	1034	105	88	12	20°
391	1250	1370	1068	105	91	12	20°
30	1260	1377	1094	123	92	12	27°
42	1260	1377	1094	123	92	12	27°
101	1276	1396	1095	106	93	12	20°
82	1285	1402	1132	97	96	12	20°
102	1290	1405	1129	100	95	12	20°
136	1293	1410	1131	121	82	14	20°
132	1295	1410	1131	117	82	14	20°
58	1295	1410	1131	117	82	14	20°
83	1297	1416	1128	120	95	12	20°
86	1300	1408	1134	122	82	14	20°
26	1300	1420	1138	110	83	14	20°
34	1300	1420	1138	108	83	14	27°
43	1340	1461	1162	120	85	14	20°
8	1340	1475	1165	120	85	14	27°
11	1340	1475	1165	120	85	14	27°
13	1340	1461	1162	120	85	14	20
144	1340	1460	1162	110	85	14	20°
91	1350	1495	1164	110	85	14	20°
4	1360	1510	1192	135	86	14	20°
179	1403	1543	1235	122	90	14	27°
135	1403	1543	1235	132	90	14	27°
85	1405	1526	1236	122	90	14	27°
115	1405	1526	1235	122	90	14	27°
113	1405	1524	1235	122	90	14	20°
5	1405	1532	1236	125	90	14	27°
134	1405	1542	1235	122	90	14	27°
322	1405	1526	1235	132	90	14	27°
27	1405	1526	1235	122	90	14	27°
133	1405	1526	1235	122	90	14	27°
174	1405	1533	1235	125	90	14	27°
105	1405	1550	1238	148	90	14	27°
137	1405	1550	1235	147	90	14	27°
112	1405	1563	1240	152	84	15	27°
14	1405	1550	1238	152	78	16	20°
70	1406	1526	1236	122	90	14	27°
138	1406	1526	1236	122	90	14	20°
15	1407	1552	1236	132	90	14	27°
106	1408	1530	1250	114	91	14	20°
107	1410	1530	1234	117	90	14	20°
111	1416	1560	1200	125	77	16	25°
117	1460	1615	1274	122	92	14	27°
49	1461	1593	1274	122	92	14	20°
148	1470	1599	1288	125	93	14	20°
46	1475	1614	1272	120	92	14	20°

烟台春晖回转支承挖机参数表

编号	滚道中心直径	外径	内径	总高	齿数	模数	压力角
7	1487	1630	1297	120	83	16	27°
128	1487	1630	1296	120	83	16	27°
131	1492	1650	1274	130	107	12	20°
162	1495	1650	1274	130	107	12	20°
130	1495	1650	1274	130	107	12	20°
68	1510	1664	1313	139	84	16	20°
114	1524	1656	1344	125	97	14	20°
153	1528	1680	1343	140	136	10	27°
116	1530	1682	1319	138	111	12	20°
44	1530	1682	1319	138	111	12	20°
118	1530	1675	1346	132	114	12	20°
122	1530	1690	1318	140	96	14	20°
103	1605	1777	1392	120	118	12	20°
156	1605	1775	1394	127	118	12	20°
158	1612	1794	1380	190	100	14	27°
171	1615	1820	1347	180	98	14	20°
163	1618	1820	1347	180	98	14	20°
160	1620	1800	1347	180	98	14	20°
172	1635	1815	1374	205	100	14	20°
161	1663	1807	1443	120	105	14	20°
129	1795	1978	1540	204	112	14	27°