



政然

## 正确的产品。合适的价格。快速交货高质量产品

The right product. The right price. Right away.

Top quality product



河北七玖 Hebei Qijiu Manufacturer 联系电话: 15132183170





## 安全信息-用户责任

胶软管的使用寿命主要取决于专用用途。安装软管的设备和系统必须进行安全设计。由于我们的软管可以设计用于不同的应 用,因此不能保证在所有情况下产品的正常功能。用户在选择满足其要求的产品时必须对与特定用途相关的技术方面进行分 因此,对于七玖公司软管的各种工作条件和应用,用户应自行负责最终选择适合于满足应用要求的性能和安全要求的产

产品数据表中显示的信息和技术数据必须由具有适当技术技能的用户检查。

七玖公司对最终用户确定的与产品目录,产品表,报价,订单确认和所附任何建议中所显示的用途不同的其他用途概不负责。 不正确的产品选择或不遵循软管的安装,使用,维护和存放程序可能会导致软管断裂,并造成材料损坏和/或严重伤害人身。 对于七玖公司产品的选择和正确使用,您还可以参考Assogomma提供的"选择,存储,使用和维护橡胶软管的建议"文档 该文档可从www.qijiu-machine.com获得。

这些建议是根据国际标准ISO 8331 "塑料和橡胶软管和软管组件-选择,储存,使用和维护准则"制定的。 出于安全原因,切勿超过产品数据表中指示的工作压力。

对于橡胶软管的特定应用,请参考法律要求或特定标准。此外,还有针对特殊关键应用的其他建议。 有关更多信息,请联系市场部(wangzihao@hbqijiu.com)。

## SAFETY INFORMATION - USER RESPONSIBILITIES

The service life of rubber hoses mainly depends on the dedicated use. Equipment and systems where the hose is installed must be designed safely. Since our hose can be designed for different applications, Qijiu company cannot guarantee the proper functioning of the product for all situations. The analysis of the technical aspects related to specific uses must be performed by the users when choosing the product that meets their requirements. So, in relation to the variety of operating conditions and applications of the Qijiu hose, the user is solely responsible for the final choice of the product deemed suitable to satisfy the performance and safety requirements called for the application.

The information and technical data shown in the product data sheets must be examined by users with appropriate technical skills.

Qijiu company is not responsible for other uses, identified by the end user, that are different from the one shown in its catalogues, product sheets, offers, order confirmations and any recommendations attached.

An inappropriate choice of the product or a failure to follow the procedures of installation, use, maintenance and storage of the hoses may lead to a hose break and cause material damage and/or serious injury to people. For the selection and proper use of the Qijiu products you can also refer to the document "Recommendations for selection, storage, use and maintenance of rubber hoses" provided by Assogomma and available on

www.gijiu-machine.com.

These recommendations are according to the international standard ISO 8331, "Plastic and rubber hoses and hose assemblies - Guidelines for selection, storage, use and maintenance."

For safety reasons, never exceed the working pressure indicated in the product data sheet.


For specific applications of rubber hoses, please refer to the legal requirements or specific standards; moreover additional recommendations for particularly critical applications are available.

For further information, contact the Marketing department (wangzihao@hbqijiu.com).





〇 内径 Hose I.D.		Q_h∕A 外径 Hose O.D.		最大工作压力 Max Operationg Pressure				重量 Weight		长度 Length	
mm	in	mm	in	Мра	Psi	Мра	Psi	Kg/m	lbs/ft	mtr	ft
51	2.00	69.5	2.72	1.50	217	6.00	870	2.68	1.80	14-70	46-230
57	2.23	74.5	2.90	1.50	217	6.00	870	2.75	1.84	14-70	46-230



## 喷浆管/干磨料输送管

Gunite hose/Dry abrasive materials delivery hose

质量标准:磨耗标准符合ISO 4649:65 +/- 5mm3

Standards: abrasion loss of the tube according to ISO 4649: 65 +/- 5mm3.

应用范围:软壁软管,用于输送散装物料,使用防静电耐磨损橡胶,用于输送水泥浆,沙子,砾石,硅石

和其他干磨料,混凝土,石膏和灰泥浆喷涂。

Application: softwall bulk materials handling hose made with antistatic and abrasion

resistant rubber. Suitable to convey cement, sand, gravel, silica, and other dry abrasive materials,

spraying of concrete, plaster, and gypsum. 温度范围: -40°C (-40°F) 到 +70°C (+158°F)

Temperature: from -40°C (-40°F) to +70°C (+158°F).软管结构

Construction

内层: 黑色,光滑,抗静电耐磨的SBR/NR 橡胶

Tube: black, smooth, NR/SBR rubber with good resistance in handling abrasive materials.

加强层: 高强力钢丝编织

Reinforcement: High strength steel wire braiding

外层: 黑色或其他颜色, 光滑(表面布纹), 抗静电耐磨的SBR/NR 橡胶

Cover: black or other colors, smooth (wrapped finish), NR/SBR rubber, abrasion resistant.

商标: 连续白色条形标记 "EUROCRETE (公司商标)…"

Branding: continuous red stripe "EUROCRETE (family logo)..." .

可选择项: 1. 不同口径2. 不同外胶颜色3. 不同工作压力

Also available upon request: 1.Different diameters 2.Cover in different colors 3.Different working pressures



