

WHEELED SCISSOR PLATFORM

6-10M

working height

PRODUCT FEATURES

- Vehicle transportation is convenient, good passability;
- Full height walking, equipped with multiple safety protection devices, high safety;
- Both sides of the overall spiral tray, daily inspection and maintenance is convenient;
- Man-machine interaction, fault diagnosis, parameter reading and writing, system monitoring;
- New energy power, small size, light weight, pollution-free;
- Dc motor drive, high efficiency, high sensitivity.

PRODUCT CONFIGURATION

- Platform self-locking door
- Work schedule
- Emergency descent system
- Automatic pothole protection
- Tilt protection system
- Automatic braking system
- Emergency stop button
- Fault diagnosis system
- Full height walk



The pictures and parameters are for reference only

TECHNICAL PARAMETER

6-10m working height							
Model number		SJPT0407 Liquid drive	SJPT0407E Motor drive	SJPT0607 Liquid drive	SJPT0607E Motor drive	SJPT0608 Liquid drive	SJPT0808 Liquid drive
Max.working height	M	6	6	7.8	7.8	8.3	10.3
Platform size	M	1.4x0.76	1.4x0.76	1.4x0.76	1.4x0.76	1.8x0.78	1.8x0.78
Platform extension dimension	M	0.6	0.6	0.6	0.6	0.9	0.9
Machine height (Fence raised)	M	1.97	1.97	2.15	2.15	2.23	2.33
Machine height (Guardrail folded)	M	1.6	1.6	1.78	1.78	1.8	1.9
Whole length	M	1.52	1.52	1.52	1.52	2.1	2.1
Whole width	M	0.76	0.76	0.76	0.76	0.81	0.81
Rated load	Kg	230	230	230	230	300	300
Driving speed (folded mode)	km/h	2	2	2	2	2	2
Max.climbing capacity	%	25	25	25	25	25	25
Wheel size	mm	Φ305x100	Φ305x100	Φ305x100	Φ305x100	Φ305x100	Φ305x100
Storage battery	·	2x12V/120Ah	2x12V/100Ah	2x12V/120Ah	2x12V/100Ah	4x12V/83Ah	4x12V/83Ah
Whole weight	Kg	830	830	994	994	1350	1450

WHEELED SCISSOR PLATFORM

12-16M

working height

PRODUCT FEATURES

- Vehicle ride optimization, superior performance;
- Full height walking, equipped with multiple safety protection devices, high safety;
- Both sides of the overall spiral tray, daily inspection and maintenance is convenient;
- Screen human-computer interaction, parameter setting, fault diagnosis, parameter reading and writing, system monitoring;
- The electrical and hydraulic design is optimized and matched, the number of cycles is high, and the endurance is provided;
- Parts universal and modular design, durable and reliable.

PRODUCT CONFIGURATION

- Full height walk
- Platform self-locking door
- Emergency descent system
- Automatic pothole protection
- Automatic braking system
- Emergency stop button
- Fault diagnosis system
- Tilt protection system



The pictures and parameters are for reference only

TECHNICAL PARAMETER

12-16m working height				
Model number		SJPT1012 Liquid drive	SJPT1212 Liquid drive	SJPT1412 Liquid drive
Max.working height	M	11.8	13.8	15.8
Platform size	M	2.27×1.12	2.27×1.12	2.67×1.12
Platform extension dimension	M	0.9	0.9	1.1
Machine height (Fence raised)	M	2.42	2.54	2.68
Machine height (Guardrail folded)	M	1.88	2	2.14
Whole length	M	2.49	2.49	2.87
Whole width	M	1.15	1.15	1.4
Rated load	Kg	450	450	450
Driving speed (folded mode)	km/h	3.5	3.5	3.5
Max.climbing capacity	%	25	25	25
Wheel size	·	Φ381×127	Φ381×127	Φ381×127
Storage battery	·	4×12V/120Ah	4×12V/120Ah	4×12V/120Ah
Whole weight	Kg	2600	2900	3900