

双缸液压剪 Excavator Hydraulic Shear

适用范围

楼房拆除、钢材等剪切作业。

核心特点

- ① 采用专用回转支撑和马达，操作灵活，性能稳定，扭矩大。
- ② 剪体采用 TDNM450 板材，韧性高，耐磨。
- ③ 刀片采用进口材料，使用寿命更长。
- ④ 结构经过优化设计，不易变形。

Applicable Fields

Demolition of buildings, cutting of steel, etc.

Product Features

- ① Adopt special slewing support and motor, flexible operation, stable performance and large torque.
- ② The shear body is made of TDNM450 plate, which has high toughness.
- ③ The blade is made of imported materials, which has a longer service life.
- ④ The structure is optimized and not easily deformed.



项目/型号	Item/model	Unit	TD100	TD150	TD200	TD300
重量	Weight	kg	500	1640	2650	3300
开口	Opening	mm	500	600	850	850
刀片长度	Blade length	mm	400	500	670	670
高度	Height	mm	1380	1880	2350	2350
宽度	Width	mm	810	1000	1350	1350
额定压力	Rated Pressure	bar	180	240	300	300
额定流量	Rated Flow	lpm	180	230	200	380
工作压力	Rated Pressure	bar	180	240	300	300
适用挖掘机	Suitable Excavator	ton	6-9	12-18	20-30	>30

