

工业轮胎 Industrial Tires

型号 MODELS	层级 PLY RATING	标准轮辋 STANDARD RIM	直径 OVERALL DIAMETER(MM)	宽度 SECTION WIDTH(MM)	负载能力 LOAD CAPACITY(KG)	压力 INFLATED PRESSURE(KPA)	有无内胎 TYPE
10-16.5	10	8.25	779	261	2170	520	TT/TL
12-16.5	12	9.75	830	312	2900	550	TT/TL
14-17.5	14	10.5	922	351	3875	550	TT/TL
15-19.5	14	11.75	1029	391	4565	485	TT/TL
11L-16	12	8.00	838	279	1250	440	TT/TL
23X8.5-12	6	7.00	574	213	820	340	TT/TL



型号 MODELS	层级 PLY RATING	标准轮辋 STANDARD RIM	直径 OVERALL DIAMETER(MM)	宽度 SECTION WIDTH(MM)	负载能力 LOAD CAPACITY(KG)	压力 INFLATED PRESSURE(KPA)	有无内胎 TYPE
10-16.5	10	8.25	779	279	2140	520	TT/TL
12-16.5	12	9.75	835	325	2885	550	TT/TL



型号 MODELS	层级 PLY RATING	标准轮辋 STANDARD RIM	直径 OVERALL DIAMETER(MM)	宽度 SECTION WIDTH(MM)	负载能力 LOAD CAPACITY(KG)	压力 INFLATED PRESSURE(KPA)	有无内胎 TYPE
10-16.5	12	8.25	792	265	2170	520	TT/TL
12-16.5	14	9.75	826	300	2865	550	TT/TL
11L-16	12	8.00	838	279	1395	420	TT/TL
12.5/80-18	16	W9	965	306	4055	480	TT/TL
14-17.5	16	10.5	945	349	3875	550	TT/TL



农业轮胎 Agricultural tires



型号 MODELS	层级 PLY RATING	标准轮辋 STANDARD RIM	花纹深度 DEEP (mm)	轮胎充气外缘尺寸 DIMENSIONS OF THE INFLATED OUTER EDGE OF THE TIRE		不同速度下负荷 LOAD AT DIFFERENT SPEEDS		不同速度下压力 PRESSURE AT DIFFERENT SPEEDS		有无内胎 TYPE
				截面宽 SECTION WIDTH	外直径 OVERALL DIAMETER	10km/h	50km/h	10km/h	50km/h	
750-16	8	5.5	20	205	810	770		280		TT/TL
8.3-24	12	W7	26	210	995	975		300		TT/TL
8.3-20	12	W7	22	210	895	850		280		TT/TL
600-14	6	4.50E	17	165	690	450		250		TT/TL
600-12	6	4.50E	18	165	640	405		250		TT/TL
700-12	8	4.50E	18	180	670	520		250		TT/TL
550-16	6	4.00E	8	150	710	525		370		TT/TL
9.5-24	12	W8	26	240	1050	1180		300		TT/TL
650-16	8	4.50E	18	180	765	620		300		TT/TL
11.2-28	10	W10	26	285	1205	1500		300		TT/TL
14.9-30	12	W13	30	378	1415	2400		270		TT/TL
12.4-28	12	W11	26	315	1260	1830		320		TT/TL
13.6-20	12	W12	28	345	1060	1750		240		TT/TL
11.2-24	12	W10	28	285	1105	1535		360		TT/TL
9.5-16	12	W8	22	240	860	875		240		TT/TL
14.9-30	12	W13	30	378	1415	2400		270		TT/TL
11-32	12	W10	30	305	1360	1530		290		TT/TL
11.2-24	12	W10	28	285	1105	1535		360		TT/TL
13.6-16	10	W12	26	345	1000	1060		150		TT/TL
13.6-24	12	W12	28	345	1210	2100		330		TT/TL