



型号 MODELS	层级 PLY RATING	标准轮辋 STANDARD RIM	轮胎充气外缘尺寸 DIMENSIONS OF THE INFLATED OUTER EDGE OF THE TIRE		不同速度下负荷 LOAD AT DIFFERENT SPEEDS		不同速度下压力 PRESSURE AT DIFFERENT SPEEDS		有无内胎 TYPE
			新宽度 SECTION WIDTH	外直径 OVERALL DIAMETER	10km/h	50km/h	10km/h	50km/h	
8.25-16	16	6.50H	235	845	1800		730		TT/TL
8.25-20	16	6.50	235	974	2120		730		TT/TL
9.00-16	16	6.50H	240	880	2430		870		TT/TL



型号 MODELS	层级 PLY RATING	标准轮辋 STANDARD RIM	轮胎充气外缘尺寸 DIMENSIONS OF THE INFLATED OUTER EDGE OF THE TIRE		不同速度下负荷 LOAD AT DIFFERENT SPEEDS		不同速度下压力 PRESSURE AT DIFFERENT SPEEDS		有无内胎 TYPE
			新宽度 SECTION WIDTH	外直径 OVERALL DIAMETER	10km/h	50km/h	10km/h	50km/h	
9.00-20	18	7.00	255	1015	4000		760		TT/TL
10.00-20	18	7.00	275	1015	4950		825		TT/TL



型号 MODELS	层级 PLY RATING	标准轮辋 STANDARD RIM	轮胎充气外缘尺寸 DIMENSIONS OF THE INFLATED OUTER EDGE OF THE TIRE		不同速度下负荷 LOAD AT DIFFERENT SPEEDS		不同速度下压力 PRESSURE AT DIFFERENT SPEEDS		有无内胎 TYPE
			新宽度 SECTION WIDTH	外直径 OVERALL DIAMETER	10km/h	50km/h	10km/h	50km/h	
9.00-20	14	7.00	255	1015	4375		725		TT/TL
	16	7.00	255	1015	4750		825		TT/TL



08

工业轮胎 Industrial Tires



型号 MODELS	层级 PLY RATING	标准轮辋 STANDARD RIM	直径 OVERALL DIAMETER(MM)	宽度 SECTION WIDTH(MM)	负载能力 LOAD CAPACITY(KG)	压力 INFLATED PRESSURE(KPA)	有无内胎 TYPE
10-16.5	12	8.25	820	264	1930	520	TT/TL
12-16.5	14	9.75	831	325	2865	550	TT/TL



型号 MODELS	层级 PLY RATING	标准轮辋 STANDARD RIM	直径 OVERALL DIAMETER(MM)	宽度 SECTION WIDTH(MM)	负载能力 LOAD CAPACITY(KG)	压力 INFLATED PRESSURE(KPA)	有无内胎 TYPE
10-16.5	12	8.25	792	265	2170	520	TT/TL
12-16.5	14	9.75	826	300	2865	550	TT/TL
12.5/80-18	16	W9	965	306	4055	480	TT/TL
16.9-28	14	W15L	1410	450	3450	300	TT/TL

型号 MODELS	层级 PLY RATING	标准轮辋 STANDARD RIM	直径 OVERALL DIAMETER(MM)	宽度 SECTION WIDTH(MM)	负载能力 LOAD CAPACITY(KG)	压力 INFLATED PRESSURE(KPA)	有无内胎 TYPE
10-16.5	12	8.25	792	265	2170	520	TT/TL
12-16.5	14	9.75	826	300	2865	550	TT/TL



09