

## 实心轮胎

Solid tyre



| 轮胎型号<br>SIZE | 适用钢圈<br>RIM  | 外直径<br>OVERALL<br>DIAMETER | 断面宽<br>SECTION<br>WIDTH | 行驶面宽<br>DRIVING<br>WIDTH | 最大负荷10KM/H<br>MAXIMUM LOAD | 最大负荷26KM/H<br>MAXIMUM LOAD |
|--------------|--------------|----------------------------|-------------------------|--------------------------|----------------------------|----------------------------|
| 23.5-25      | 19.25/25     | 1580                       | 550                     | 520                      | 19500                      | 14500                      |
| 17.5-25      | 14.00/1.5    | 1327                       | 412                     | 394                      | 13000                      | 10500                      |
| 16/70-20     | 13.00        | 1016                       | 388                     | 377                      | 4075                       | 3875                       |
| 20.5/70-16   | 10.00 (9.5)  | 895                        | 284                     | 277                      | 6450                       | 5350                       |
| 28*9-15      | 7.00         | 691                        | 208                     | 190                      | 4090                       | 3270                       |
| 650-10       | 5.00         | 566                        | 153                     | 145                      | 2840                       | 2110                       |
| 300-15       | 8.00         | 788                        | 238                     | 234                      | 5900                       | 4700                       |
| 700-12       | 5.00         | 643                        | 176                     | 163                      | 3015                       | 2410                       |
| 825-15       | 6.50         | 810                        | 204                     | 192                      | 4940                       | 3950                       |
| 1200-20      | 8.00/8.50-20 | 1086                       | 282                     | 271                      | 8800                       | 7000                       |
| 100-20       | 7.50/8.00-20 | 1038                       | 264                     | 255                      | 7240                       | 5795                       |
| 900-20       | 6.50/7.00-20 | 948                        | 222                     | 210                      | 6450                       | 5460                       |
| 825-20       | 6.50/7.00-20 | 933                        | 212                     | 200                      | 5425                       | 4340                       |
| 12-16.5      | 9.75-16      | 820                        | 273                     | 264                      | 4375                       | 3875                       |
| 10-16.5      | 8.0-16       | 756                        | 255                     | 239                      | 4230                       | 3080                       |
| 825-16       | 6.50         | 825                        | 218                     | 211                      | 4980                       | 4000                       |
| 750-16       | 5.5/6.0/6.5  | 787                        | 187                     | 174                      | 3910                       | 3130                       |
| 650-16       | 5.50         | 723                        | 157                     | 148                      | 2950                       | 2215                       |
| 250-15       | 7.50         | 724                        | 234                     | 222                      | 4366                       | 3400                       |
| 825-12       | 5.00         | 696                        | 189                     | 181                      | 3326                       | 2660                       |
| 200/50-10    | 6.50         | 441                        | 187                     | 127                      | 2370                       | 1900                       |
| 23*9-10      | 6.50         | 561                        | 191                     | 184                      | 4005                       | 3205                       |
| 700-9        | 5.00         | 536                        | 157                     | 150                      | 2370                       | 2015                       |
| 600-9        | 4.00         | 515                        | 143                     | 131                      | 1920                       | 1535                       |
| 21*8-9       | 6.00         | 505                        | 192                     | 182                      | 2810                       | 2250                       |
| 18*7-8       | 4.33         | 440                        | 155                     | 150                      | 2350                       | 1880                       |
| 16*6-8       | 4.33         | 404                        | 147                     | 135                      | 1500                       | 1200                       |
| 5.00-8       | 3.00         | 400                        | 111                     | 102                      | 1055                       | 845                        |

## 轮式挖掘机轮胎

Wheel excavator tire

○驱动性好，耐磨，耐刺扎，耐掉块，加深的花纹设计，有效延长使用寿命。  
适用于：小型轮式挖掘机等工程机械。

○Optimized deepen pattern design for small excavator. Excellent traction with abrasion, puncture and cut resistance, long service life.

| 型号<br>MODELS | 层级<br>PLY<br>RATING | 标准钢圈<br>STANDARD<br>RIM | 轮胎充气外缘尺寸<br>DIMENSIONS OF THE INFLATED<br>OUTER EDGE OF THE TIRE | 不同速度下负荷<br>LOAD AT DIFFERENT<br>SPEEDS | 不同速度下压力<br>PRESSURE AT DIFFERENT<br>SPEEDS | 有无内胎<br>TYPE |
|--------------|---------------------|-------------------------|------------------------------------------------------------------|----------------------------------------|--------------------------------------------|--------------|
| 7.50-16      | 14                  | 6.00                    | 215 805                                                          | 10km/h 50km/h                          | 10km/h 50km/h                              | TT/TL        |
| 8.25-16      | 16                  | 6.50                    | 235 855                                                          | 2450                                   | 875                                        | TT/TL        |

| 型号<br>MODELS | 层级<br>PLY<br>RATING | 标准钢圈<br>STANDARD<br>RIM | 轮胎充气外缘尺寸<br>DIMENSIONS OF THE INFLATED<br>OUTER EDGE OF THE TIRE | 不同速度下负荷<br>LOAD AT DIFFERENT<br>SPEEDS | 不同速度下压力<br>PRESSURE AT DIFFERENT<br>SPEEDS | 有无内胎<br>TYPE |
|--------------|---------------------|-------------------------|------------------------------------------------------------------|----------------------------------------|--------------------------------------------|--------------|
| 8.25-16      | 16                  | 6.50                    | 235 855                                                          | 10km/h 50km/h                          | 10km/h 50km/h                              | TT/TL        |

| 型号<br>MODELS | 层级<br>PLY<br>RATING | 标准钢圈<br>STANDARD<br>RIM | 轮胎充气外缘尺寸<br>DIMENSIONS OF THE INFLATED<br>OUTER EDGE OF THE TIRE | 不同速度下负荷<br>LOAD AT DIFFERENT<br>SPEEDS | 不同速度下压力<br>PRESSURE AT DIFFERENT<br>SPEEDS | 有无内胎<br>TYPE |
|--------------|---------------------|-------------------------|------------------------------------------------------------------|----------------------------------------|--------------------------------------------|--------------|
| 8.25-16      | 16                  | 6.50                    | 235 845                                                          | 2560 1800                              | 875 730                                    | TT/TL        |

