



型号 MODELS	层级 PLY RATING	标准轮辋 STANDARD RIM	花纹深度 DEEP (mm)	轮胎充气外缘尺寸 DIMENSIONS OF THE INFLATED OUTER EDGE OF THE TIRE		不同速度下负荷 LOAD AT DIFFERENT SPEEDS		不同速度下压力 PRESSURE AT DIFFERENT SPEEDS		有无内胎 TYPE
				断面宽 SECTION WIDTH	外直径 OVERALL DIAMETER	10km/h	50km/h	10km/h	50km/h	
23.1-26	12	Dw20	16	595	1500	5050	3610	200	200	TT/TL
13.00-25	28	8.50	27	350	1300	8000	4250	825	550	TT/TL
1400-24	28	10.00	31	450	1310	8500	4625	700	475	TT/TL
900-20	20	7.0		255	1015	4750		825		TT/TL
1000-20	20	7.5		278	1073	3260		670		TT/TL
1100-20	22	8		290	1080	6000		825		TT/TL
1200-24	20	8.50		325	1000	6900	3750	825	550	TT/TL
13/80-20	24	8.50		315	1245	6000		900		TT/TL
1300-24	12	8.00		330	1278	5600	2725	450	300	TT/TL
1400-24	12	8.00		360	1350	6400	3075	450	300	TT/TL
15.5-25	16	12.00/1.3		395	1275	5600	3250	400	300	TT/TL
20.5-25	20	17.00/2.0		520	1490	8250	4500	350	275	TT/TL
17.5-25	16	14.00/1.5		445	1350	7300	4250	475	300	TT/TL
23.5-25	20	19.50/2.5		595	1615	9500	5450	350	250	TT/TL



叉车轮胎 Forklift tire



○耐磨性能好，加深花纹，承载能力强、抗扭曲性能强、适合叉车作业。

○It has good wear resistance, deep tread pattern, strong load-bearing capacity, strong resistance to twisting, and is suitable for forklift operations.

型号 MODELS	层级 PLY RATING	标准轮辋 STANDARD RIM	轮胎充气外缘尺寸 DIMENSIONS OF THE INFLATED OUTER EDGE OF THE TIRE		不同速度下负荷 LOAD AT DIFFERENT SPEEDS		不同速度下压力 PRESSURE AT DIFFERENT SPEEDS		有无内胎 TYPE
			断面宽 SECTION WIDTH	外直径 OVERALL DIAMETER	10km/h	50km/h	10km/h	50km/h	
300-15	20	8.00	300	840	5530				TT/TL
825-15	16	6.50	188	825	3185			830	TT/TL
28"9-15	14	7.00	202	689	2575			970	TT/TL
23"9-10	16	5.00	200	590	2870			720	TT/TL
825-12	12	6.50	170	710	2585			720	TT/TL
700-12	12	5.00	156	664	2005			860	TT/TL
700-9	12	5.00	155	580	1995			860	TT/TL
650-10	10	5.00	140	578	1400			790	TT/TL
600-9	10	4.00	138	535	1275			860	TT/TL
500-8	10	3.50	114	467	845			790	TT/TL
18"7-8	14	4.33	154	454	1870			790	TT/TL

