HA16JE/RJE Lead-acid or Lithium

GB/CE/ANSI Compliance

HIGHLIGHTS

- AC motor drive, smooth driving, better micro mobility.
- High-precision overload sensing system to reduce accidental and false alarm shutdown.
- Smoother slew ensured by integrated slewing reducer; comprehensive protections suitable for dusty environments.
- Smoother actions and more energy saving thanks to zero-emission devices
- Large capacity battery with strong endurance.



Configurations Standard

Horn
Proportional Controls
Motion Alarm
Flashing Beacons
Emergency Descent System
Emergency Stop
AC Power to the Platform
Automatic Leveling Platform
Fault Diagnosis System
Overload Sensing System
Self-lock Gate
Anti-extrusion device


Optional


Air Pipe to the Platform

Let customers win first


A-Boom Lift Show MOBILE ELEVATING WORK PLATFORMS

MODEL	HA16JE	HA16JE-Li	HA16RJE-Li
Max.Working Height	17.7m	17.7m	17.7m
Max. Platform Height	15.7m	15.7m	15.7m
Max. Horizontal Extension	9.13m	9.05m	9.23m
Max.Up and Over Height	7.6m	7.63m	7.6m
A- Length (Stowed)	6.98m	6.86m	6.98m
B- Width (Stowed)	1.95m	1.95m	1.95m
C- Height (Stowed)	1.96m	2m	1.96m
D- Platform Length	1.52m	1.8m	1.52m
E- Platform Width	0.76m	0.76m	0.76m
F- Wheelbase	2.01m	2.01m	2.01m
G- Ground Clearance	0.23m	0.23m	0.23m
PERFORMANCE			
Platform Capacity	230kg	230kg	230kg
Max.Drive Speed (Stowed)	4.8km/h	4.8km/h	4.8km/h
Gradeability	30%	30%	30%
Turning Radius(In.)	0.8m	0.8m	0.8m
Turning Radius(Out.)	3.8m	3.8m	3.8m
Turntable Rotation	355°Non-Continuous	355°Non-Continuous	355°Non-Continuous
Vertical JIB rotation	/	/	±80°
Platform Rotation	±80°	±80°	±85°
H- Turntable Tailswing	0.08m	0.15m	0.08m
Tilt Rating	4.5°	4.5°	4.5°
Operating Wind Speed	12.5m/s	12.5m/s	12.5m/s
Lift Motor	5kw	5kw	5kw
Drive Motor	5kw	5kw	5kw
POWER			
Batteries(V/Ah)	48V/310Ah	51.2V/280Ah	51.2V/280Ah
Charger	100-240VAC/13.5A	100-240VAC/13.5A	100-240VAC/13.5A
Tires	705X210X445	705X210X445	705x210x445
WEIGHT			
Weight	7850kg	7950kg	7850kg





HA16JE/HA16JE-LI



HA16RJE