HZ0821EA

GB/CE/ANSI Compliance

HIGHLIGHTS

- Extra-large platform, superb load capacity, and fast yet stable lifting performance greatly enhance work efficiency.
- Flexible and fast chassis leveling capability, fearless of complex working environments, with one-key leveling.
- Four-wheel drive and floating axle design easily handle rough terrains.
- AC motor drive ensures smooth travel and excellent fine movement control.



Configurations Standard

Work strobe light	Automatic braking system
Emergency stop button	Proportional control
Extension platform	Tilt protection system
Emergency descent system	Folding guardrails
Floating axle	Platform self-locking door
Working hour meter	Fault diagnosis system
Motion buzzer	Charging protection system
Horn	GPS
AC Power to the Platform	

Optional

Working Lamp on the Platform
Load Sensing System
Air Pipe to the Platform Outriggers

Let customers win first

Rough Terrain Lift MOBILE ELEVATING WORK PLATFORMS

MODEL	HZ0821EA
Max.Working Height	10.1m
A-Max. Platform Height(In/out)	8.1m
B-Platform Length	3.68m
C-Platform Width	1.81m
Extension Size	0.9m
D-Heights (Rails Up)	2.79m
Height (Rails Down)	1.98m
E-Length (with Ladder)	3.91m
F-Overall Width	2.1m
G-Wheel Base	2.54m
H-Ground Clearance	0.2m
PERFORMANCE	
Platform Capacity	770kg
Extension Capacity	320kg
Max. Occupancy(indoor)	5
Max.Drive Speed (Stowed)	4.8km/h
Drive Speed (Raised)	0.6km/h
Turning Radius (In.)	2.35m/5.2m
Up/Down Time	30s/35S
Gradeability	35%
Max. Slope	14° 10°
Control	Proportional Control
Drive	Four-Wheel
Multi Disc Brake	Four-Wheel
Tires (mm)	26X12-16
Max.Wind Speed	12.5m/s
POWER	
Batteries (V/Ah)	48V/310Ah
Charger	100-240VAC/13.5A
WEIGHT	
Weight	4970KG





