HC0607EA

GB/CE/ANSI Compliance

HIGHLIGHTS

- Simple layout and easy maintenance and service.
- Pure electric drive with zero emissions, low noise, and strong gradeability.
- Neutral steering feature suitable for complicated working conditions.
- Long battery endurance.

Configurations Standard

Automatic Braking System
One-Way Extension Platform
Folding Guardrails
platform self-lock door
Charging Protection System
Proportional Control
Emergency Decent System
Motion Alarm
Emergency Stop
Tilt Protection System
Safety access support bar
Fault Diagnosis System
Forklift Hole
Flashing Beacons
Hour meter
Horn
Load Sensing System
AC Power to the Platform

Optional

Air Pipe to the Platform



Let customers win first

Crawler Leveling Lift MOBILE ELEVATING WORK PLATFORMS

MODEL	HC0607EA
A-Max. Platform Height(In/out)	5.9m
Max.Working Height	7.9m
B-Platform Length	1.67m
C-Platform Width	0.74m
Extension Size	0.9m
D-Heights (Rails Up)	2.39m
Height (Rails Down)	2.06m
E-Length (with Ladder)	2.02m
F-Overall Width	1.47m/1.3m
G- Ground Clearance	80mm
PERFORMANCE	
Platform Capacity	250kg
Extension Capacity	113kg
Max. Occupancy(in/out)	2/1
Drive Speed (Stowed)	2.4km/h
Turning Radius	Rotate in Place
Up/Down Time	16/34s
Gradeability	40%
Max. Slope	X(20°/-16°) ;Y(14°/-14°)
Drive	Rear Crawler
Crawler (mm)	250mmX72mmX60
POWER	
Batteries (V/Ah)	8X12V/160Ah
Charger	100-240VAC/13.5A
WEIGHT	
Weight	1890kg







