



TUBOMATIC H83 ES

Code: **TUBH83ES**

CRIMPING (STANDARD VOLUME CRIMPING)
扣压机 (标准产量型)



ALSO AVAILABLE WITH
PORTABLE DIES HOLDER
可提供便携
发散式模具柜



TUBOMATIC H83 EL

Code: **TUBH83EL**

CRIMPING (STANDARD VOLUME CRIMPING)
扣压机 (标准产量型)



MAIN FEATURES - 主要特点



Ideal for any type of fitting

可扣压各种形式
胶管接头



MACH touch-screen
electronic control

MACH数控系统

H83 ES



Electro-mechanical
control

电动控制面板

H83 EL



Warning LED

LED报警提示

H83 EL



Vernier dial

游标刻度盘

H83 EL



Ideal for your workshop

车间的理想选择

TECHNICAL DATA - 技术参数		
	H83 ES	H83 EL
CRIMPING FORCE 扣压力	180 TON	180 TON
6 SPIRALS 2 PIECES 6 层	1"	1"
MAX Ø 扣压后最大尺寸	62 mm ♦	62 mm ♦
CRIMPING/HOUR 扣压次数/小时	1083 ■	1083 ■
DIE OPENING 模具张开量	Ø + 42 mm	Ø + 42 mm
90° FITTINGS 90° 胶管接头	1" 1/4	1" 1/4
STANDARD VOLTAGE 标准电压	375V-420V 50HZ 3PH	375V-420V 50HZ 3PH
MOTOR POWER 电机功率	4 Kw (5 Hp)	4 Kw (5 Hp)
DIMENSIONS LxWxH 尺寸 长x宽x高	690x617x760 mm	690x650x665 mm
WEIGHT WITHOUT OIL 净重 (不含油)	220 Kg	220 Kg
OIL (NOT INCLUDED) 液压油 (不包含)	70 Lt.	70 Lt.
USB KIT USB 接口	■	-

ACCESSORIES - 附件 (可选配)			
		H83 ES	H83 EL
PRESSURE CONTROL SYSTEM KIT 压力控制系统		■	-
QUALITY CHECK: PRESSURE AND DIAMETER COMBINED CONTROL 质量检测系统: 压力与尺寸配合控制		■	-
MULTISTEP CRIMPING DIAMETERS 多尺寸设定系统		■	-
DISPENSER + PATENTED QUICK CHANGE TOOL 发散式模具柜 + 专利的快速切换工具		■	■
ELECTRIC PEDAL 脚踏板		■	■
BASE 底座		■	■
BACK MIRROR 后视镜		■	■

Diameter (mm) 模具尺寸 (mm)	10	12	14	16	19	22	25	29	34	38	42	46	50
H83 ES	DIES LENGTH (mm) / 模具长度 (mm)												
H83 EL	60	60	60	60	60	60	60	70	70	85	85	85	86

■ THEORETICAL WITH 1/2" Δ Ø 6 MM HOSE - ♦ WITH SPECIAL DIES Ø 54 MM UPON REQUEST - ● WITH SPECIAL DIES
■ 1/2" Δ Ø 6 MM 软管为理论数据 - ♦ 根据需求可提供特制模具 Ø 54 MM - ● 使用特制模具
ALL CAPACITIES INDICATED DEPEND ON THE KIND OF FITTING USED - 所有标注的加工范围取决于所使用的接头类型

Product specifications could be modified without prior notice.
产品说明如有更改, 恕不另行通知。