

挖掘机链轨技术数据表

Parameter for Excavator track link Assembly



序号	型号	T	A	B	C	D	d	ØE	F	G	H	J	K	L	通用机型Machine
1	W90GA	90				22.2	115.2		27	80	59		46	23	EX30 PC20/30 YC35*43L
2	W101GA	101	55	55	22	32	19	10.5	35	94	76	40	63	37	EX30 PC20/30 YC35*43L
3	W135GA	135	85	55	46	35	22.5	12.5	31.6	114	78.6	41	65	35	PC40-5
4	W135GB	135	93.8	63.8	46	35	22.5	12.5	40.4	124	87.4	41	65	35	PC40-7*40L PC55
5	W135GC	135	99	72	43.2	42	24	12.5	44	141	108	42.5	75	40	PC60-5*42L
6	W135GD	135	99	72	43.2	39.2	22.5	12.5	44	141	108	42.5	75	40	DH55*40L
7	W135GE	135	106	76	47	41	24	12.5	44	141	108	42.5	75	40	E70B*42L E307
8	W135GF	135	104	80	46	35	22.3	12	53.6	141	108	40	65	35	R60-5*40L ZAX55 IH155
9	W135GH	135	88.4	64.4	46	35	22.3	12	41	123	89	40	65	35	SWE50*39L
10	W135GI	135	98.4	74.4	46	35	22.3	12	51	133	99	40	65	35	YC60-5*41L
11	W140GA	140	86	86	52	42	28	14.5	55	139	115	44	75	41	YC85*42L
12	W154GA	154	90	90	55	46.3	30	14.5	56	158	127	49	80	42	EX60*37L
13	W154GA	154	74	74	55	46.3	30	14.5	56	158	127	49	80	42	JBT185
14	W154GB	154	89	73	57	41.2	24	14.5	45	130	104.2	44	74	40.5	PC60-6/7*38L EX70*38 SK60 SH70
15	W154GC	154	112.4	82.4	57	46.3	30	14.5	49.4	161	125.4	44	87	47	PC100-3*46L D31*39L FR85*39
16	W160GA	160	99	99	56	45	30	14.5	64	161	135	52	83	46	D9*44
17	W171GA	171	108	108	60.3	47	30	16.5	58.6	170	129	55.57	90.2	49.5	SK100*41L SK120*44L
18	W171GB	171	108	108	60.3	50.3	33.5	16.5	70	181	144.8	55.57	95	51	EX120*43L E312 E120B SH120*44L EC140*46L
19	W171GC	171	144.5	125.4	58.7	54	36.65	16.5	87.7	212	171.7	56.3	101.6	58.8	R200*50L SE210-1 SE210LC*54L R210LC-2
20	W175GA	175	102.4	86.4	57	46.3	30	16.5	50.4	165	122.4	54	86	46	PC120-5*42L SY150
21	W175GB	175	158.4	122.4	57	55.26	36.6	18.5	84.6	214	173.2	54	101.5	56.5	HD700 DH800
22	W175.4GA	175.4	144.5	125.4	58.7	58.75	36.6	18.5	77.5	214	170	57.2	103.2	59.7	EX200-1*48L SH280*49L
23	W190GA	190	155.6	119.6	69	58.8	36.6	20.5	82.2	215	174.2	58	106	60	E200B*45L SH200*46L HD820*48LE324 SK260*51L
24	W190GB	190	160.4	124.4	62	59	38	18.5	85.6	215	176	58	105	58	PC200-3*46L EX200-2/5*46L ZX210*46L
25	W190GC	190	160.4	124.4	62	59	38	20.5	85.6	215	176	58	105	58	PC200-5*45L DH220*49L R225 EC210
26	W203GA	203	178.4	138.4	72	66.8	44.6	20.5	101.6	244	201.6	58	116.4	64.4	EX300-1*47L DH300*51L HD1430*48L
27	W203GC	203	179	129	72	64	42	20.5	94	235	194	62	115	64	E325*45L
28	W203GE	203	186.2	148.2	76.2	66.8	44.6	19.5	112.4	248	212.4	58	116.4	64.4	R944*51L FH300
29	W203GC	203	163	113	72	64	42	20.5	94	218	194	62	115	64	R934 ATLASD3306
30	W216GA	216	178.4	140.4	76.2	66.5	44.6	22.5	101.6	242	197.6	63	116	64	PC300-6*45L PC360 EX360 R305
31	W216GB	216	184	146	76.2	71.6	47	22.5	106	252	209.2	63	129	70	EX400-1*49L DH500*53L EC360*50L
32	W216GC	216	190	140	76.2	68	46	22.5	103	248	211	69	124	68	E330*45L SK330 SK350*48L E330LC*49L
33	W216GB	216	184	146	76.2	71.6	47	24.5	106	252	209.2	63	129	70	PC400/5*49L EX450*49L EC460*52L EX470*53L
34	W228GA	228	184	144	76.2	71.6	47	24.5	109	254	210	71.4	129	70	PC400-6*46L PC450*46L SY460*49L
35	W228GB	228	200	149.2	76.2	74.3	49	24.5	112	264	214	71.4	131	72	SK460*50L CX470 SH450
36	W260GA	260	235	184.2	76.2	85.3	57.3	27.5	133	321	266.2	87.3	152	79	EX870*47L EC700 E375
37	W260GB	260	235	184.2	76.2	85.3	57.3	30.5	133	321	266.2	87.3	152	79	E390 E385

推土机链轨技术数据表

Parameter forBulldozer track link Assembly



序号	型号	T	A	B	C	D	d	ØE	F	G	H	J	K	L	通用机型Machine
1	T135GA	135	99	72	43.2	41.3	24	12.5	45	141	105	42.5	75	40	D20
2	T140GA	140	94	94	52	42	28	12.5	63	146	123	44	75	41	ATLAS D7*50L
3	W149GA	149	84.2	84.2	57	38	25	14.5	55	139	115	46	77	41.8	CW341 ECM350
4	T155GA	155.6	88.9	88.9	57.15	43.22	28.9	13.5	59.4	157	125	49.2	76.2	41.3	TPJ1250 CAT933C
5	T155GB	155.6	104.7	88.9	54.8	47.1	28.55	14.8	60	159	127.9	48.7	88	49	D3C
6	T171GA	171	108	108	60.3	54	33.5	16.5	70	181	144.8	55.57	95	51	EX120*43L E312 E120B SH120*44L EC140*46L
7	T171GB	171	143.8	103.8	57	56	33.5	18.5	74.8	190	137.7	54	98	55	D4H
8	T175.4GA	175.4	144.5	125.4	58.7	58.75	36.5	16.5	77.5	214	170	57.2	103.2	59.7	D5 D5B
9	T175GA	175	158.4	122.4	57	55.26	36.6	18.5	84.6	214	173.2	54	101.5	56.5	D40 D50 HD700
10	T203GA	203	178.4	138.4	72	69	44.6	20.5	101.6	244	201.6	58	116.4	64.4	D65 SD16
11	T203GB	203	184	146	72	66	44.6	20	108	252	208	60	115	63	T140*37L T160
12	T203GC	203	171.4	133.4	76.2	66.7	44.6	19.5	102.4	232	193.2	58	121.5	69	D6D
13	T203GD	203	185	137.3	68	70	44.6	20	101.3	232	193.2	64	125	72	D6H
14	T216GA	216	184	146	76.2	73.4	47	20.5	106	252	209.2	63	129	70	D80 D85 SD22
15	T216GB	216	204.1	146.1	63	81.5	47.7	23	104	252	226	68.8	150	85	D8N
16	T228GA	228	219	169	76.2	79	48.5	24.5	121.6	292	244	71.4	138	78	D155*41 E350 TY320-41 ZAX650*52L ZAX500*49L
17	T228GB	228	201.6	169.8	76.2	76.2	50.8	23	124.4	292	246.8	71.4	138	78	D8K
18	T260GA	260	235	184.2	76.2	89	55.8	27.5	133	321	266.2	87.3	152	79	D355*39L EX870*47L EC700 E375
19	T280GA	280	256.6	183	79.5	100	60.2	34	130.8	331	306.4	91.5	181	105	PC1250
20	T317GA	317	92	92	58	47	30	16.5	43	170	103	55.57	90.2	49.5	D475

产品型号表示方式: X XXX X X
同一规格产品序号
SERIAL NO. OF SAME TYPE(L,R,C,D,B)
产品结构形式: G—干式
STRUCTURE TYPE: G—DRY HOUS
字母代号
字母代号
V: 挖掘机系列; T: 推土机系列
V: EXCAVATOR SERIES; T: BULLDOZER SERIES

