

PTO 驱动的属具

匹配拖拉机的路拌机	拖拉机 (hp)	PTO (rpm)	工作宽度 (mm)	总宽度 (mm)	重量 (Kg)	工作深度 (mm)
STABI/FRS	300-500	1000	2320-2560	2750-2990	6300-6750	500
STABI/H	300-500	1000	2293-2533	2664-2904	7300-7500	165-560
匹配拖拉机的多功能机	拖拉机 (hp)	PTO (rpm)	工作宽度 (mm)	总宽度 (mm)	重量 (Kg)	工作深度 (mm)
MTL	140-300	1000	1480-2440	1820-2780	3370-4370	150-280 (G/3) 150-280 (R)
MTM	220-360	1000	2053-2293	2495-2735	5950-6500	240-400 (G/3) 250-400 (R)
MTH	300-500	1000	2320-2560	2901-3141	7900-8325	320-500 (G/3) 340-500 (R)

数据为相应产品系列的最小值和最大值。
详细信息请参阅具体型号的技术参数表。

DP062010 ZH - 06/2026 - 由 FAE S.p.A. 提供



建筑施工 PTO 驱动的属具



PTO 驱动的属具

FAE 建筑施工系列的 PTO 驱动的属具适用于稳定土的拌合，石头、水泥路面和沥青路面的破碎。可匹配小马力、中马力、和大马力的拖拉机使用。

该系列包括路拌机和粉碎拌合多功能机。

路拌机



300-500 hp



50 cm
(最大)

适用于稳定土拌合



多功能机



140-500 hp



50 cm (最大)

石头破碎、路面破碎、稳定土拌合——集多种功能于一身。



扫码了解更多关于
建筑产线中 PTO
驱动的信息。

