

PTO DRIVEN HEADS

SOIL STABILIZERS FOR TRACTORS	Tractor (hp)	PTO (rpm)	Working width (mm)	Total width (mm)	Weight (Kg)	Working depth (mm)
STABI/FRS	300-500	1000	2320-2560	2750-2990	6300-6750	500
STABI/H	300-500	1000	2293-2533	2664-2904	7300-7500	165-560
MULTITASKS FOR TRACTORS	Tractor (hp)	PTO (rpm)	Working width (mm)	Total width (mm)	Weight (Kg)	Working depth (mm)
MTL	140-300	1000	1480-2440	1820-2780	3370-4370	150-280 (C/3) 150-280 (R)
MTM	220-360	1000	2053-2293	2495-2735	5950-6500	240-400 (C/3) 250-400 (R)
MTH	300-500	1000	2320-2560	2901-3141	7900-8325	320-500 (C/3) 340-500 (R)

The data refers to the minimum and maximum values of the product ranges.
Refer to the technical table of the specific model for more details.

DP062001 EN – 04/2026 – by FAE Group S.p.A.



CONSTRUCTION PTO Driven Heads



PTO DRIVEN HEADS

FAE's PTO driven heads in the Construction line are designed for mixing, stabilizing, crushing and shredding. The line offers solutions for low, medium, high and extremely high horsepower tractors. The product line includes soil stabilizers and multitask heads that can be used for a wide variety of tasks.

SOIL STABILIZERS



300-500 hp



56 cm max

For soil mixing and stabilization, also with special binders.



MULTITASKS



140-500 hp



50 cm max

Stone crushing, mixing, stabilizing, shredding - all in one multitask head.



LEARN MORE ABOUT
THE PTO DRIVEN
HEADS FROM THE
CONSTRUCTION LINE

