

# K-80

## 轮式滑移装载机

Wheel Skid-steer Loader



原地转向  
一机多用

K-80主要技术参数 Main Technical Parameters of K-80

|               |                                              |                                                                                                                                |
|---------------|----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| 额定工作载荷 (kg)   | Rated Working Load                           | 350                                                                                                                            |
| 操作重量 (kg)     | Operating weight                             | 1250                                                                                                                           |
| 举起力 (铲斗) (n)  | Min Qili (Bucket)                            | 1873                                                                                                                           |
| 掘起力 (动臂) (kg) | Hori Qili (Boom)                             | 1784                                                                                                                           |
| 最大行走速度 (km/h) | Maximum walking speed                        | 10.5                                                                                                                           |
| 发动机           | engine                                       | 可选配: 常柴(国四、欧五), 莱动(国二、国四、欧五)<br>Optional: Changchai (China Stage IV, Euro V), Laidong (China Stage II, China Stage IV, Euro V) |
| 扭矩 (nm)       | Torque                                       | 140.4                                                                                                                          |
| 排量 (L)        | Displacement                                 | 1.218                                                                                                                          |
| 汽缸数           | Number of cylinders                          | 3                                                                                                                              |
| 燃油            | fuel oil                                     | 柴油 Diesel                                                                                                                      |
| 功率 (Kw)       | Power                                        | 18.5                                                                                                                           |
| 燃油箱 (L)       | Fuel tank                                    | 24.5                                                                                                                           |
| 行走方式          | Mode of movement                             | 轮式 Wheeled                                                                                                                     |
| 长*宽*高 (mm)    | Length × Width × Height                      | 2427*901*1814                                                                                                                  |
| 设备转向          | Equipment redirection                        | 方向和速度均由左右两侧手柄控制<br>Direction and speed are both controlled by the left and right joysticks.                                    |
| 设备举升和倾卸       | Equipment lifting and unloading              | 单独由左右两侧脚踏板控制<br>Controlled separately by left and right foot pedals.                                                           |
| 前液压辅助装置 (标准)  | Front Hydraulic Assistance Device (Standard) | 由右侧手柄控制<br>Controlled by the right joystick.                                                                                   |