



UNIFLEX KS 6、KS 8和KS 10专为精密压接和校准而设计。



KS 6, KS 8, KS 10

技术参数	KS 6	KS 8	KS 10
扣压力 (kN/Ton)	500/50	800/80	1,800/180
免润滑：摩擦力减少20%	✓	✓	✓
控制	Control C.2	Control C.2	Control C.2
最大扣压范围 (mm)	55	139	139
开口 (mm)	+27.5	+45	+45
无模具开口 (mm)	91.5	190	190
模具系列	PBK 266	PBK 237	PBK 237
速度 (mm/sec)			
关闭	12	7	3.5
扣压	12	7	3.5
张开	30	15	6
噪声	58 dBA	58 dBA	58 dBA
驱动	5.5 kW 3~VAC	5.5 kW 3~VAC	5.5 kW 3~VAC
液压油	80 l	80 l	80 l
长 x 宽 x 高 (mm)	1,000 x 1,000 x 1,700	1,000 x 1,000 x 1,700	1,000 x 1,000 x 1,700
重量 (kg)	470	570	570
选项			
IPC	✓	✓	✓

模具系列	
	PBK 266
Ø mm	mm
6.8	3
8	3
9	3
10	3
11	3
12	3
14	4
16	4
17	4
19	4
20	4.5
22	4.5
24	4.5
25	4.5
28	5
30	5
32	5
34	5
36	5
39	5
40	5
44	5
47	5

模具系列	
	PBK 237
Ø mm	mm
12	3
14	3
16	4
17	4
19	4
22	4.5
24	4.5
26	4.5
28	4.5
32	5
36	5
40	5
44	5
46	5
47	5
50	5
54	5
57	5
62	5
67	5
71	5
74	5
78	5
84	5
86	5
90	5
96	5
103	5
106	5