

Outrigger Crane Pads

Checkers™ outrigger crane pads are made from a special formulation high-quality polyethylene—they will not splinter, crack, are non-conductive, and will not absorb water. They are easy to install and provide a safe working environment for heavy equipment with outrigger arms. The unique design allows each pad to adapt to the working surface and return to its original shape once the work is complete.

These strong and durable products are easy to clean, are chemical and oil resistant, easy to store, and long-lasting. These outrigger pads are an efficient and cost-effective solution for outrigger support. Despite being incredibly strong and durable, the pads have a lightweight design making them easy to install and move around. As they're impermeable to water, they can be used in all weather conditions and their hard-wearing structure makes them unbreakable during normal working conditions.

- High load capacity designed to fully support vehicles and cranes without warping or splintering
- Engineered to bend but not break
- Recovery memory after bending restores original shape
- Safety textured surface and orange tough grip handles improve grip and stability



Model	Load capacity*	45 deg. load capacity*	Length	Width	Thickness	Weight	Prop 65
PAD1515.75	45,000 lb (20,412 kg)	20,000 lb (9,072 kg)	15 in (38.1 cm)	15 in (38.1 cm)	0.75 in (1.9 cm)	5.5 lb (3.4 kg)	—
PAD18181	55,000 lb (24,948 kg)	30,000 lb (13,608 kg)	18 in (45.7 cm)	18 in (45.7 cm)	1 in (2.5 cm)	11 lb (5 kg)	—
PAD24241	60,000 lb (27,216 kg)	35,000 lb (15,876 kg)	24 in (61 cm)	24 in (61 cm)	1 in (2.5 cm)	20 lb (9.1 kg)	—
PAD24242	62,000 lb (28,123 kg)	40,000 lb (18,144 kg)	24 in (61 cm)	24 in (61 cm)	2 in (5 cm)	38 lb (17.2 kg)	—
PAD30301	81,000 lb (36,741 kg)	41,000 lb (18,598 kg)	30 in (76.2 cm)	30 in (76.2 cm)	1 in (2.5 cm)	31 lb (14 kg)	—
PAD36361	93,000 lb (42,185 kg)	43,000 lb (19,505 kg)	36 in (91.4 cm)	36 in (91.4 cm)	1 in (2.5 cm)	45 lb (20.4 kg)	—
PAD48481	135,000 lb (61,236 kg)	52,000 lb (23,587 kg)	48 in (122 cm)	48 in (122 cm)	1 in (2.5 cm)	80 lb (36.3 kg)	—
PAD30302	85,000 lb (38,556 kg)	43,000 lb (19,505 kg)	30 in (76.2 cm)	30 in (76.2 cm)	2 in (5 cm)	62 lb (28 kg)	—
PAD36362	98,000 lb (44,253 kg)	45,000 lb (20,412 kg)	36 in (91.4 cm)	36 in (91.4 cm)	2 in (5 cm)	90 lb (40.8 kg)	—
PAD48482	140,000 lb (63,504 kg)	55,000 lb (24,948 kg)	48 in (122 cm)	48 in (122 cm)	2 in (5 cm)	160 lb (72.6 kg)	—

*Load bearing capacity is subject to ground conditions. Sizing is subject to a manufacturing variance of +/- 5%.