


Automotive Relay

ITEM NO.	APPLICATION	MODEL NO.	SPECIFICATION	PHOTO	REFERENCE NO. / OE NO.
1	Universal	JD125A-08B	Rated voltage:12VDC Load current:25A Contact material: AgSnO2 No. of terminal: 4 pins Material of terminal:brass Size: 22.4*15.4*25.5mm Terminal length: 12mm Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form:1A		
2	HOWO	JD220A-09A	Rated voltage:24VDC Load current:25A Contact material: AgSnO2 No. of terminal: 4 pins Material of terminal:brass Size: 22.4*15.4*25.5mm Terminal length: 12mm Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form:1A		WG9725584002
3	Universal	JD125C-08B	Rated voltage:12VDC Load current:25A/20A Contact material: AgSnO2 No. of terminal: 5 pins Material of terminal:brass Size: 22.4*15.4*25.5mm Terminal length: 12mm Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form:1C		
4	HOWO	JD220C-09A	Rated voltage:24VDC Load current:25A/20A Contact material: AgSnO2 No. of terminal: 5 pins Material of terminal:brass Size: 22.4*15.4*25.5mm Terminal length: 12mm Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form:1C		WG9725584003
5	Universal	JD130A-23	Rated voltage:12V Load current:30A Contact material: AgSnO2 No. of terminal: 4 pins Material of terminal:brass x3, iron x1 Size: 23.0*15.0*25.5mm Terminal length: 11mm Working temperature:-40℃- +85℃ Contact form:1A		

6	Universal	JD130C-23	Rated voltage:12V Load current:30A/20A Contact material: AgSnO2 No. of terminal: 5 pins Material of terminal:brass Size: 23.0*15.0*25.5mm Terminal length: 11mm Working temperature:-40℃- +85℃ Contact form:1C		
7	Universal	JD130C-02	Rated voltage:12VDC Load current:30A/20A Contact material: AgSnO2 No. of terminal: 5 pins Material of terminal:brass Size: 23.0*15.0*25.5mm Working temperature:-40℃- +85℃ Contact form:1C		
8	Universal	JD120A-19A	Rated voltage:12V Load current:20A Contact material: AgSnO2 No. of terminal: 4 pins Material of terminal:brass Size: 29.0*19.0*29.5mm Terminal length: 11mm Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form:1A		
9	Universal	JD125A-20A	Rated voltage:12V Load current:25A Contact material: AgSnO2 No. of terminal: 4 pins Material of terminal:brass Size: 30.0*26.0*30.5mm Terminal length: 11mm Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form:1A		
10	Universal	JD140A-21	Rated voltage:12V Load current:40A Contact material: AgSnO2 No. of terminal: 4 pins Material of terminal:brass Size: 28.0*23.0*29.5mm Terminal length: 11mm Working temperature:-40℃- +85℃ Contact form:1A		
11	Universal	JD111A-01	Rated voltage:12V Load current:30A Contact material: AgSnO2 No. of terminal: 3 pins Size: 50.5*31.0*30.4mm Terminal length: 12.7mm Working temperature:-40℃- +85℃ Contact form:1A		JL2AA-12V
12	Universal	JD211A-01	Rated voltage:24V Load current:30A Contact material: AgSnO2 No. of terminal: 3 pins Size: 50.5*31.0*30.4mm Terminal length: 12.7mm Working temperature:-40℃- +85℃ Contact form:1A		JL2BB-24V



13	Universal	JD140C-07	Rated voltage:12V DC Load current:40A/30A No. of terminal: 5 pins Contact form:1C Contact material: AgSnO2 Material of terminal: brass Size: 27.4mm*28.4mm*25.0mm Terminal length: 11.3mm Working temperature:-40℃- +85℃		
14	Universal	JD140A-07	Rated voltage:12V DC Load current:40A No. of terminal: 4 pins Contact form:1A Contact material: AgSnO2 Material of terminal: brass Size: 27.4mm*28.4mm*25.0mm Terminal length: 11.3mm Working temperature:-40℃- +85℃		
15	Universal	JD140C-07A	Rated voltage:12V DC Load current:40A/30A No. of terminal: 5 pins Contact form:1C Contact material: AgSnO2 Material of terminal: brass Size: 27.4mm*28.4mm*25.0mm Terminal length: 11.3mm Working temperature:-40℃- +85℃		
16	Universal	JD140A-07A	Rated voltage:12V DC Load current:40A No. of terminal: 4 pins Contact form:1A Contact material: AgSnO2 Material of terminal: brass Size: 27.4mm*28.4mm*25.0mm Terminal length: 11.3mm Working temperature:-40℃- +85℃		
17	Universal	JD140C-07C	Rated voltage:12V DC Load current:40A/30 A Contact form:1C Contact material: AgSnO2 No. of terminal: 5 pins Material of terminal:brass Size: 27.4mm*28.4mm*25.0mm Terminal length: 11.3mm Working temperature:-40℃- +85℃		
18	Universal	JD140C-07C	Rated voltage:12V DC Load current:40A/30 A Contact form:1C Contact material: AgSnO2 No. of terminal: 5 pins Material of terminal:brass Size: 27.4mm*28.4mm*25.0mm Terminal length: 11.3mm Working temperature:-40℃- +85℃		
19	Universal	JD140C-07D	Rated voltage:12V DC Load current:40A/30A No. of terminal: 5 pins Contact form:1C Contact material: AgSnO2 Material of terminal: brass Size: 27.4mm*28.4mm*25.0mm Terminal length: 11.3mm Working temperature:-40℃- +85℃		

20	Universal	JD140A-25FU	Rated voltage:12V DC Load current:40A Contact form:1A Contact material: AgSnO2 No. of terminal: 4 pins Material of terminal:brass Size: 36.8mm*27.0mm*23.3mm Terminal length: 11.3mm Working temperature:-40℃- +85℃		
21	Universal	JD1402A-26A	Rated voltage:12V DC Load current:2 X 20A Contact material: AgSnO2 No. of terminal: 5 pins Material of terminal:brass Size: 28.0mm*28.0mm*26.0mm Terminal length: 11.0mm Working temperature:-40℃- +85℃ Contact form:2A		
22	Universal	JD140A-31A	Rated voltage:12V DC Load current:40A No. of terminal: 4 pins Contact form:1A Contact material: AgSnO2 Material of terminal: brass Size: 26.0mm*26.0mm*24.0mm Terminal length: 11.3mm Working temperature:-40℃- +85℃		
23	Universal	JD140A-31D	Rated voltage:12V DC Load current:40A No. of terminal: 4 pins Contact form:1A Contact material: AgSnO2 Material of terminal: brass Size: 26.0mm*26.0mm*24.0mm Terminal length: 11.3mm Working temperature:-40℃- +85℃		
24	Universal	JD140A-31	Rated voltage:12V DC Load current:40A No. of terminal: 4 pins Contact form:1A Contact material: AgSnO2 Material of terminal: brass Size: 26.0mm*26.0mm*24.0mm Terminal length: 11.3mm Working temperature:-40℃- +85℃		
25	BEIBEN Others	JD240A-06	Rated voltage:24V Load current:40A Contact material: AgSnO2 No. of terminal: 4 pins Material of terminal: brass Size: 28.0*28.0*25.3mm Terminal length: 11.0mm Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form: 1A		2075450105
26	BEIBEN Others	JD240C-06L	Rated voltage:24V Load current:40A Contact material: AgSnO2 No. of terminal: 5 pins Material of terminal: brass Size: 28.0*28.0*25.3mm Terminal length: 11.0mm Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form: 1C		2075450205

27	MAN NEOPLAN SHACMAN	JD2402A-05	Rated voltage:24V Load current:40A Contact material: AgSnO2 No. of terminal: 5 pins Material of terminal: brass Size: 28.0*28.0*25.0mm Terminal length: 11.0mm Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form:2A		81.25902.0410
28	MAN NEOPLAN SHACMAN	JD2402A-06	Rated voltage:24V Load current:40A Contact material: AgSnO2 No. of terminal: 5 pins Material of terminal: brass Size: 28.0*28.0*25.0mm Terminal length: 11.0mm Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form:2A		81.25902.0459
29	MAN NEOPLAN SHACMAN	JD240C-06	Rated voltage:24V Load current:40A Contact material: AgSnO2 No. of terminal: 5 pins Material of terminal: brass Size: 28.0*28.0*25.0mm Terminal length: 11.0mm Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form:1C		81.25902.0460
30	MAN NEOPLAN SHACMAN	JD270A-04A	Rated voltage:24V Load current:70A Contact material: AgSnO2 No. of terminal: 4 pins Material of terminal: copper, brass Size: 33.2*31.3*31.5mm Terminal length: 14.5mm, 11mm Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form: 1A		81.25902.0317
31	MAN NEOPLAN SHACMAN	JD270A-04B	Rated voltage:24V Load current:70A Contact material: AgSnO2 No. of terminal: 4 pins Material of terminal: copper, brass Size: 33.2*31.3*31.5mm Terminal length: 14.5mm, 11mm Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form: 1A		81.25902.0415
32	Universal	JD180A-01A	Rated voltage:12V DC Load current:80A No. of terminal: 4 pins Contact form: 1A Contact material: AgSnO2 Material of terminal:30,87: copper, 85,86:brass Size: 27.4mm*28.4mm*25.0mm Terminal length: 14.0mm Working temperature:-40℃- +85℃		
33	Universal	JD180A-01	Rated voltage:12V DC Load current:80A No. of terminal: 4 pins Contact form: 1A Contact material: AgSnO2 Material of terminal:30,87: copper, 85,86:brass Size: 27.4mm*28.4mm*25.0mm Terminal length: 14.0mm Working temperature:-40℃- +85℃		

34	Universal	JD180A-01D	Rated voltage:12V DC Load current:80A No. of terminal: 4 pins Contact form:1A Contact material: AgSnO2 Material of terminal:30,87: copper, 85,86:brass Size: 27.4mm*28.4mm*25.0mm Terminal length: 14.0mm Working temperature:-40℃- +85℃		
35	Universal	JD180C-01	Rated voltage:12V DC Load current:80A/60A No. of terminal: 5 pins Contact form:1C Contact material: AgSnO2 Material of terminal:30,87,87A: copper, 85,86:brass Size: 27.4mm*28.4mm*25.0mm Terminal length: 14.0mm Working temperature:-40℃- +85℃		
36	Universal	DK175-61	Rated voltage:12V DC Load current:75A No. of terminal:4 pins Contact form: 1A Contact material: AgSnO2 Size: 74.8mm*32.3mm*39.0mm Working temperature:-40℃- +85℃		TE:V23232-D0001-X001 Bosch 0332002150
37	Universal	DK175-61DD	Rated voltage:12V DC Load current:75A No. of terminal:4 pins Contact form: 1A Coil protection: diode Contact material: AgSnO2 Size: 74.8mm*32.3mm*39.0mm Working temperature:-40℃- +85℃		TE:V23232- A0001- X003 V23232-A0001- Y003 Bosch 0332002156
38	Universal	DK1120-21	Rated voltage:12VDC Load current:100A/120A Contact material: AgSnO2 Size: 46.0*46.0*44.5mm Material of studs: brass Stud size: M6 Working temperature:-40℃- +85℃ Contact form:1A		
39	Universal	DK1200-21	Rated voltage:12VDC Load current:200A Contact material: AgSnO2 Size: 46.0*46.0*44.5mm Material of studs: copper Stud size: M6 Working temperature:-40℃- +85℃ Contact form:1A		
40	Universal	DK1200-21S	Rated voltage:12VDC Load current:200A Contact material: AgSnO2 Size: 43.8mm*33.5mm (L*H) Material of studs: copper Stud size: M6 Working temperature:-40℃- +85℃ Contact form:1A		

41	Universal	DK1200-21M-1A	Rated voltage:12V DC Load current:200A Contact form:1A Contact material: AgSnO2 Size: 46.0mm*46.0mm*44.5mm Studs: copper M8 Working temperature:-40℃- +85℃		
42	Universal	DK1200-21M-1C	Rated voltage:12V DC Load current:200A Contact form:1C Contact material: AgSnO2 Size: 46.0mm*46.0mm*44.5mm Studs: copper M8 Working temperature:-40℃- +85℃		
43	Universal	DK1100-03	Rated voltage:12VDC Load current:100A Contact material: AgSnO2 Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form:1A		TE V23132-A2002-B200 GAZ 1393315-2
44	Universal	DK2100-03	Rated voltage:24VDC Load current:100A Contact material: AgSnO2 Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form:1A Application: HOWO AUMAN	N.A.	TE V23132-B2002-B200
45	Universal	DK1150-03	Rated voltage:12VDC Load current:150A Contact material: AgSnO2 Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form:1A	N.A.	V23132-A2002-B200
46	Universal	DK2150-03	Rated voltage:24VDC Load current:150A Contact material: AgSnO2 Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form:1A	N.A.	V23132-B2002-B200
47	Universal	DK1150-58	Rated voltage:12V DC Load current:150A No. of terminal:4 pins Contact form:1A Coil protection: resistor Contact material: AgSnO2 Working temperature:-40℃- +85℃		

48	Universal	DK1150-58X	Rated voltage:12V DC Load current:150A No. of terminal:4 pins Contact form:1A Coil protection: resistor Contact material: AgSnO2 Cable:15cm Working temperature:-40℃- +85℃		
49	Universal	DK1150-58J	Rated voltage:12V DC Load current:150A No. of terminal:4 pins Contact form:1A Coil protection: resistor Contact material: AgSnO2 Cable: 15cm Connector: DJ7021-1.5-20 Working temperature:-40℃- +85℃		
50	Universal	DK1300-62	Rated voltage:12V DC Load current:300A No. of terminal:4 pins Contact form:1A Contact material: AgSnO2 Working temperature:-40℃- +85℃		
51	JMC Other	DK1200-04	Rated voltage:12VDC Load current:200A Contact material: AgSnO2 Size: 60.0*66.5*73.5mm Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form:1A		HN1 11576 AB
52	Universal	DK1150-02	Rated voltage12VDC Load current: 150A Contact material: AgSnO2 Size: 52.5*66.5*72.0mm Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form:1A		
53	Universal	DK2150-02	Rated voltage:24VDC Load current: 150A Contact material: AgSnO2 Size: 52.5*66.5*72.0mm Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form:1A		
54	SINOTRUK Other	DK2200-06	Rated voltage:24VDC Load current:200A Contact material: AgSnO2 Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form: 1A		WG9725584012

55	Universal	DK1400-05	Rated voltage:12VDC Load current:200A Contact material: AgSnO2 Size: 67.0*74.0*85.0mm Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form:1A		
56	SHACMAN Other	DK2400-05	Rated voltage:24VDC Load current:200A Contact material: AgSnO2 Size: 67.0*74.0*85.0mm Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form:1A		DZ97189763010
57	Universal	DK1300-02	Rated voltage:12VDC Load current:300A Contact material: AgSnO2 Size: 67.0*74.0*83.2mm Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form:1A		
58	Universal	DK2300-02	Rated voltage:24VDC Load current:300A Contact material: AgSnO2 Size: 67.0*74.0*83.2mm Electrical life:>=50,000 cycles Working temperature:-40℃- +85℃ Contact form:1A		