

HANFA Crawler Drilling Rig

HFQ65



HANFA GROUP

E-mail: info@hanfagroup.com

Phone: 0086-371-55019187 0086-371-55019184 0086 17739786040

Address: Room 602, Building 7, E-commerce Industrial Park,
Dongqing Street, High-tech Zone, Zhengzhou, Henan, China.

Web: WWW.HANFAGROUP.COM WWW.HANFAMACHINE.COM



涵发集团
HANFA GROUP

HANFA HFQ65 Crawler Drilling Rig



HFQ65 high pressure down hole drilling crawler open type drilling rig has the superior technical performance of low energy consumption, high efficiency, easy transportation and on-site construction, the vehicle movement mechanism is realized by the hydraulic system, and only the source of punch blower consumption, which saves the procurement cost of the whole set of equipment.

Specification	HQ65 Split Drilling Rig
Air pressure (MPa)	1.2-2.5
Air consumption (m ³)	10-20
Dust collector	Fully hydraulic dry de-dusting(optional)
Drilling diameter (mm)	100-180
Drill pipe specification (mm)	76/89/102
Drilling depth (m)	65
One-time advance stroke (mm)	3700
Compensating stroke (mm)	1000
Maximum lifting force (N)	48000
Skid steer tilt angle (°)	Up and down altogether 100
Skid steer swing angle (°)	Left and right altogether 100
Drill arm swing angle (°)	Left and right altogether 70
Drill arm tilt angle (°)	Up and down altogether 60
Chassis Ground Clearance (mm)	310
Chassis frame leveling angle(°)	±13
Traveling speed(km/h)	0-2.5
Power head torque(N-m)	3600
Power head speed(rpm)	0-120
Engine power(kw)	Cummins(National II)93kw/2200rpm
Overall dimensions(LXWXH)(mm)	5900 *2100*2200
Gross weight	5500kg (excluding drilling tools and dust removal)