

摆动快速连接器
TILTING QUICK HITCH COUPLER

适用对象
0.8-36吨挖掘机

- 产品特点

 - 左右倾斜70-90度;
 - 无外漏油缸，更稳定可靠;
 - 双保险设计，弹簧保险适应更恶劣工况，保养方便;
 - 高性能板材优化整机重量，产品更耐用;
 - 大行程设计，可适配不同轴距属具。

Applications

Fit to 0.8-36 ton excavator

- Main features

 - Tilt $\pm 70^{\circ}$ to 90° .
 - There are no exposed cylinders, It is very safe and stable.
 - Double-locking safety design. The powerful spring safety lock can work in very tough working environments. Easy maintenance.
 - Using high strength steel to increase durability and to reduce weight.
 - Variable pin center design allows you to easily pick up attachments with different pin center distances.



类别/ Category	Unit	JT-00	JT-01A	JT-01B	JT-02	JT-04	JT-06	JT-08	JT-10
摆动流量 Tilt Necessary Flow	lpm	1.8-2.4	2.8-4.0	4.3-6.8	7.6-10	14-19	18-24	28-37	60-80
摆动缸角度Tilt Degree	°	180	180	180	180	180	140	140	120
摆动缸工作压力Tilt Working Pressure	bar	210	210	210	210	210	210	210	210
连接器工作压力Quick Coupler Working Pressure	bar	25-300	25-300	25-300	25-300	25-300	25-300	25-300	25-300
必要流量 Necessary Flow	lpm	15-25	15-25	15-25	15-25	15-25	15-25	15-25	15-25
轴直径 Pin Diameter	mm	20-30	35-40	35-40	40-45	50-55	60-65	70-80	90-100
尺寸 Overall Dimension (L*W*H)	mm	396*220*436	458*283*532	458*283*532	587*322*582	634*348*640	815*396*756	830*496*822	1095*638*1075
设备重量 Weight	kg	56	82	120	180	220	385	594	1150
适用挖机 Suitable Excavator	ton	0.8-1.5	2-3.5	2-3.5	4-6	7-9	10-15	16-28	28-36