



旋转抓石(钢)器

ROTATING STONE/ SCRAP STEEL GRAPPLE



适用对象

抓玉石、大理石等珍贵石材，抓废铁。

产品特点

- M+S马达带刹车功能，油缸带美国SUN安全平衡阀；
- 根据需求可做加宽型，下抓可定做3+2,4+3,5+4；
- 电控和液控系统带美国SUN节流阀和减压阀、溢流阀，更安全稳定，操作方便故障率低。

Applications

Stones, steel and iron scraps demoliting, Scrap handling, Cleaning, Moving, Loading, Sorting and Organizing materials in order.

Main features

- Driven by M+S motor with brake valve,cylinder with USA safety valve(USA SUN brand).
- Custom service is available.(3+2, 4+3, 5+4 fingers for your option).
- Throttle, pressure reducing valve, relief valve (all the valves are USA SUN brand)are in electrical and hydraulic control system, making it safer and much more stable and durable in use.

类别t/ Category	Unit	JT-01	JT-02	JT-04	JT-06	JT-08	JT-10
旋转角度 Rotation Angle	°	360	360	360	360	360	360
夹口尺寸 Max Jaw Opening	mm	1108	1247	1350	1650	2375	2493
马达压力 Motor Pressure	bar	90-110	110-120	110-120	130-150	130-150	130-150
马达流量 Necessary Flow	lpm	20-30	30-40	30-40	40-50	40-50	40-50
油缸压力 Oil Cylinder Pressure	bar	160-200	160-200	160-200	180-230	180-230	200-250
油缸流量（单条） Oil Cylinder Flow	lpm	5-15	12-25	15-25	30-40	55-65	80-95
油缸推力 Oil Cylinder Force	ton	3.8	7	10	15.7	30.7	38.5
外形尺寸 Dimension L*W*H	mm	1160*520*398	1342*595*405	1385*646*405	1765*805*550	2127*980*675	2330*1021*812
设备重量 Weight	kg	230-250	390*410	420-450	790-820	1450-1480	2050
适配挖机 Suitable Excavator	ton	3-4	4-6	6-9	12-16	17-25	26-35