
山东路得威工程机械制造有限公司
SHANDONG ROADWAY CONSTRUCTION MACHINERY MANUFACTURING CO., LTD.
High-Tech Zone Jining Shandong China. **TEL:86-537-2239258 FAX:86-537-5160603** E-mail: roadway@163.com

Traffic Index Line Remove Machine RWXB22





The milling drum adopts the conical teeth of large milling machines, which have high working efficiency and long service life.



A hydraulic control system independently designed and manufactured with core technologies



The Japanese YANMAR diesel engine is powerful,fuel-efficient and environmentally friendly.



The combined instrument control console equipped with a microcomputer can monitor the machine status and issue fault alarms in real time.

ROADWAY 山东路得威工程机械制造有限公司
SHANDONG ROADWAY CONSTRUCTION MACHINERY MANUFACTURING CO., LTD.
High-Tech Zone Jining Shandong China. **TEL:86-537-2239258 FAX:86-537-5160603** E-mail: roadway@163.com



The gear pump is assembled with high efficiency and shock resistance.



The electric control handle controls multiple working functions,making the operation convenient and smooth.



Discharging mode: lift-dump type



The discharge port is equipped with spray nozzles for dust removal and environmental protection.



The traveling wheels of the machine can be automatically hydraulically raised and lowered to adapt to various working conditions.



The walking wheels are equipped with solid tires to adapt to working on harsh ground conditions.



The dust removal box is equipped with a differential pressure sensor to intelligently control the vibration cleaning of the filter element .



Hydraulic power interface, which can be externally connected to auxiliary tools such as cutting machines and crushing picks.

Type	RWXB22	Type	RWXB22
Milling drum		Recovery bin	
Milling width	230mm	Bin capacity	1m³
Milling depth	0-10mm	Discharge time	Lift & Dump
Milling accuracy	0.2mm	Filter material	Coated self-cleaning paper filter
Milling drum diameter	300mm	Filter cleaning	High-pressure gas reverse blowing
Engine		Speed	
Model	YANMAR,4TNV98CT	Working speed	0-25m/min
Type	Diesel,four cylinder	Running speed	0-8km/h
Emission	National IV	Size and weight	
Power	53.7kW/2100rpm	Outline dimensio	3850×1960×2220mm
Fuel tank volum	200L	Weight	4550kg