ROADWAY 山东路得威工程机械制造有限公司
SHANDONG ROADWAY CONSTRUCTION MACHINERY MANUFACTURING CO., LTD.
High-Tech Zone Jining Shandong China. **TEL:86-537-2239258 FAX:86-537-5160603** E-mail: roadway@163.com

Plate compactor RWBH31B

It is used to tamper engineering foundation, road margin and asphalt surface on constructing road, street,building, ditch and bridge in the field of road, municipal engineering, construction and water conservancy etc. It is better used tamping of narrow lane way.

HONDA engine, excellent performance, easy to start-up;

Manganese alloy steel plate or nodular cast iron plate, anti-friction and anti-vibration;

NSK bearing and MITSUBOSHI V-belt;

Hydraulic reversing

Plastic treated, anti-rust, anti-corrosion and beautiful.

Move front / rear by hydraulic



HONDA engine



Transitions for short distance





Strengthen vibration plate

ROADWAY 山东路得威工程机械制造有限公司
SHANDONG ROADWAY CONSTRUCTION MACHINERY MANUFACTURING CO., LTD.
High-Tech Zone Jining Shandong China. **TEL:86-537-2239258 FAX:86-537-5160603** E-mail: roadway@163.com

Technical parameters

Type	RWBH31B
Walking	
Speed	0-23m/min
Climbing Capacity in theory	25%
Compaction	
Nominal amplitude	0.5mm
Vibrating frequency	75Hz
Exciting force	30kN
Water tank volume	12L
Engine	
Model	HONDA GX160
Type	Gasoline engine, air cooled, 4 stroke, OHV, single cylinder
Power	5.5hp/3600rpm
Fuel tank volume	3.6L
Dimension	
Plate size	710x430mm
Packing size	910x560x1450mm
Total length(keep handrail level)	1480mm
Total width	430mm
Total height（keep handrail upright）	1330mm
Weight	
Weight	165kg