# CT26
## CRAWLER EXCAVATOR

**Environment Protection Reliable Low Energy Consumption**




- Standard cab with optional canopy
- Yanmar Euro V, EPA4 engine
- Swing boom
- Imported or domestically produced load sensitive
- Zero-tail

| Specifications | Unit | CT26B | CT26BH |
|---|---|---|---|
| Operating weight | T | 2.78 | 2.78 |
| Bucket capacity | $m^3$ | 0.08 | 0.08 |
| Engine model | | YANMAR 3TNV80F | YANMAR 3TNV80F |
| Rated power | kw/r/min | 15.2/2500 | 15.2/2500 |
| Max.flow | L/min | 72 | 76.8 |
| Working pressure | Mpa | 22 | 23.5 |
| Fuel tank capacity | L | 35 | 35 |
| Hydraulic oil tank capacity | L | 28 | 28 |
| Travel speed | km/h | 2.0/3.2 | 2.4/4.5 |
| Swing speed | r/min | 11.5 | 10 |
| Max. climbing degree | % | 58 | 58 |
| Arm digging force | KN | 14.2 | 14.8 |
| Bucket digging force | KN | 20 | 24.5 |
| Average grounding pressure | Kpa | 30.5 | 31 |

| Working Range | Unit | CT26B | CT26BH |
|---|---|---|---|
| O-Max. digging height | mm | 4132 | 4132 |
| P-Max. dumping height | mm | 2742.0 | 2742 |
| Q-Max. digging height | mm | 2485 | 2485 |
| R-Max. vertical wall digging depth | mm | 2240.0 | 2240 |
| T-Max. digging reach | mm | 4610 | 4610 |
| U-Max. digging reach at ground level | mm | 4494.0 | 4494 |

| Overall Dimension | Unit | CT26B | CT26BH |
|---|---|---|---|
| A-Overall length | mm | 4159 | 4159 |
| B-Overall width | mm | 1550 | 1550 |
| C-Overall height (to top of boom) | mm | 1636.0 | 1636 |
| D-Overall height (to top of cab) | mm | 2560 | 2560 |
| E-Counterweight ground clearance | mm | 535.0 | 535 |
| F-Min. ground clearance | mm | 320 | 320 |
| G-Tail swing radius | mm | 775.0 | 775 |
| H-Track ground length | mm | 1600 | 1600 |
| J-Track length | mm | 2040.0 | 2040 |
| K-Track gauge | mm | 1250 | 1250 |
| L-Track width | mm | 1550.0 | 1550 |
| M-Track shoe width | mm | 250 | 250 |












